



	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision	UTP / COAXIAL TRANSMITTER EOC-110KIT 2 PCS SET
		
	5555.86 SEK 5555.86 SEK	640.36 SEK 640.36 SEK
Sensor	CMOS	...
LAN ports	...	1 pcs RJ45 1 pcs BNC socket
Matrix size	2 Mpx	...
Transmission speed	...	10 / 100 Mbps Half Duplex
Resolution	1280 x 720 - 720p	...
Transmission range	...	200 m @ RG6
Cards support	13.56 MHz S50	...
Main features	...	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks
Face recognition distance	0.3 m ... 1.5 m	...
Memory	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events 	...
Standard	TCP/IP	...
IR illuminator	—	...
LED illuminator	—	...
Video output	—	...
RS-485 interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	—	...
Audio	Speaker built-in	...
Network interface	10/100/1000 Mbps (RJ-45)	...
Network protocols	TCP/IP, ISUP, ISAPI	...
WEB Server	Built-in	...
ONVIF	—	...
Default IP address	192.168.1.64	...

Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	port 8000	...
Main features	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status 	...
Power supply	12 V DC / 2 A (power adapter included)	...
Power consumption	≤ 24 W	...
Housing	Metal	...
Color	Black / Silver	...
"Index of Protection"	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.31 kg	0.055 kg (single element)
Dimensions	173 x 83 x 23 mm (without bracket)	72 x 25 x 25 mm (single element)
Supported languages	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian	...
Manufacturer / Brand	Hikvision	...
SAP Code	302917454	...
Guarantee	3 years	2 years