



	MONITORS DESK MOUNT AX-PIXEL-TWIN RED EAGLE	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR DS-7204HUHI-K1/P 4 CHANNELS Hikvision
		
	34.85 CAD 34.85 CAD	396.85 CAD 396.85 CAD
Mounting standard	VESA 75, 100	...
Standard	...	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Screen size range	13 " ... 27 "	...
Bearing capacity	2 x 8 kg	...
Tilt adjustment	-60 ° ... 60 °	...
Horizontal rotation	360 °	...
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / PAL
Rotation in the plane of the screen	360 °	...
Video outputs	...	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs	...	4 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Image records resolutions	...	<ul style="list-style-type: none"> • HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 , 5.0 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • AHD : 5.0 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 8.3 Mpx - 3840 x 2160

Recording speed adjustment	...	1 ... 25 fps @ 3840 x 2160 px IP 1 ... 8 fps @ 3840 x 2160 px 1 CH only 1 ... 8 fps @ 1920 x 2160 px 1 ... 12 fps @ 2560 x 1944 px 1 ... 15 fps @ 2560 x 1440 px 1 ... 18 fps @ 1920 x 1536 px 1 ... 25 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 for each channel
Operation modes	...	4 x HD-TVI / AHD / HD-CVI / PAL / IP + 4 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
Bitrate	...	32 ... 10240 kbps
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. All channels synchronous playback, Smart Search function Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100 Base-TX
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500
Default IP address	...	DHCP or 192.168.1.64
Default admin user / password	...	admin / -
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	4 / 1
USB	...	2 pcs USB 2.0
Serial ports	...	RS-485
PTZ control	...	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection	...	✓

Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis, : intrusion, crossing the line (tripwire), scene changing • PoC - The PoC (Power over Coaxial) technology used in the device allows to power the compatible with this standard cameras via a coaxial cable directly from the recorder, eliminating the need for additional wires or power supplies
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	...	48 V DC / 1.35 A (power adapter included)
Power consumption	...	< 40 W (without HDD)
Color	Black	Black + Graphite
Weight	2.99 kg	1.25 kg
Dimensions	805 x 518 x 100 mm	315 x 250 x 47 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	RED EAGLE	Hikvision
SAP Code	...	300219949
Guarantee	2 years	3 years

