






	<a href="#">SCREWS FOR MOUNTING FIBER OPTIC ADAPTERS SM-AD*P100</a>	<a href="#">TV OR MONITOR MOUNT AX-SATURN RED EAGLE</a>	<a href="#">VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI</a>	<a href="#">BATTERY-FREE WIRELESS DOORBELL WITH 230V AC OUTLET WDP-91H2 AC 230V EURA</a>	<a href="#">CABLE OUTLET DPK1.01/11-SIMON54</a>
					
	2.79 EUR 2.79 EUR	22.21 EUR 22.21 EUR	38.02 EUR 38.02 EUR	24.44 EUR 24.44 EUR	5.30 EUR 5.30 EUR
Signaling mode	...	...	...	Sound signaling	...
Support	...	...	...	...	Simon 54 product series, for Nature, Premium frames
Number of ring-tones	...	...	...	58	...
Number of modules	...	...	...	...	1
In package	<b>100 pcs The price for package</b>	...	...	...	...
Volume adjustment	...	...	...	max. 85 dB / 1 m	...
thread	Ø 2.2 x 9.5 mm	...	...	...	...
Operation range	...	...	...	max. 100 m in open area	...
Standard	...	...	<ul style="list-style-type: none"> <li>AHD - 4 Mpx</li> <li>HD-CVI - 720p</li> <li>CVBS - PAL / NTSC</li> </ul>	...	...
Frequency band	...	...	...	433.92 MHz	...
Number of inputs	...	...	1 pcs BNC	...	...
Number of outputs	...	...	1 pcs BNC	...	...
Mounting standard	...	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400	...	...	...
Input impedance	...	...	75 Ω	...	...
Screen size range	...	23 " ... 56 "	...	...	...
Output impedance	...	...	75 Ω	...	...
Bearing capacity	...	45 kg	...	...	...
Housing	...	...	...	...	Non-halogen plastic, PC
Galvanic (optical) isolation between signal inputs and outputs	...	...	1000 V peak	...	...
Opto-isolation between power and signal inputs / outputs	...	...	1000 V peak	...	...
Distance from mounting surface	...	81 ... 360 mm	...	...	...
Color	...	Black	...	...	White (RAL 9003)
Gain adjustment	...	...	-3 dB ... +3 dB	...	...
Tilt adjustment	...	-12 ° ... 12 °	...	...	...
Main features	...	...	...	<ul style="list-style-type: none"> <li>The doorbell button is powered by an electromagnetic transducer, does not require any battery</li> <li>Wireless doorbell + 1 grounded outlet 16A/250V CEE 7/5</li> </ul>	<ul style="list-style-type: none"> <li>Cable diameter : 6.2 ... 14.5 mm</li> <li>Claw or screw mounting</li> <li>Installation in flush-mounted enclosures</li> <li>Aesthetic and solid construction</li> </ul>
Bandwidth	...	...	33 MHz / 1 Vpp	...	...
Horizontal rotation	...	-90 ° ... 90 °	...	...	...
Power supply	...	...	12 V DC / 90 mA	<ul style="list-style-type: none"> <li>230 V AC - Wireless doorbell,</li> <li>Electromagnetic transducer - Doorbell button</li> </ul>	...
Rotation in the plane of the screen	...	—	...	...	...
"Index of Protection"	...	...	...	<ul style="list-style-type: none"> <li>IP55 - Doorbell button</li> <li>IP20 - Wireless doorbell</li> </ul>	IP20

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	...	...	...	• -18 °C ... 40 °C - Doorbell button • 0 °C ... 45 °C - Wireless doorbell	...
Weight	...	4.02 kg	0.088 kg	• 0.044 kg - Doorbell button • 0.1 kg - Wireless doorbell	0.048 kg
Dimensions	Ø 3.9 x 10.9 mm	433 x 150 x (81 ... 360) mm	120 x 62 x 30 mm	• 38 x 85 x 23 mm - Doorbell button • 62 x 102 x 74 mm - Wireless doorbell	• 75 x 75 x 55 mm • 22 mm - mounting depth
Manufacturer / Brand	...	RED EAGLE	DELTA	EURA	KONTAKT Simon
Guarantee	...	2 years	3 years	2 years	6 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00