



	NVR BCS-L-NVR3202-A-4K 32 CHANNELS BCS Line	ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/100 BOTTLE 100 ml AG TERMOPASTY
		
	1230.20 AUD 1230.20 AUD	2.36 AUD 2.36 AUD
Standard	TCP/IP	...
Supported resolutions	max. 32 Mpx	...
Package	...	Bottle 100 ml
Application	...	Ideal for removing dirt from optical components
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Audio support	32 Channels - Audio from cameras	...
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Bitrate	max. 384 Mbps	...
Supported hard drives	2 x 16 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> Records searching: by time and events type. Records playback: forward, backward, fast, slow 1/4/9/16 channel synchronous playback 	...
Network interface	1 x RJ-45, 10/100/1000 Base-TX	...
Network functions	<ul style="list-style-type: none"> Live image view, Playback the records, Backup the records, remote access, CMS application Web-Server built-in 	...
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register	...
ONVIF	✓	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> Android: Free application BCS Manager iOS (iPhone): Free application BCS Manager 	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...

RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	<ul style="list-style-type: none"> • 1 pcs USB 2.0 • 1 pcs USB 3.0 	...
Serial ports	RS-485, RS-232	...
Alarm inputs / outputs	4 / 2	...
PTZ control	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : 10 rules - object detection (people, vehicle) • face detection • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Face recognition • Support for up to 20 face databases, including 20 000 face images • SMD PLUS - searching for an object classified as: human, motor vehicle • Cooperation with POS (Point of Sale) terminals - POSNET <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 4 A (power adapter included)	...
Power consumption	max. 10 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	1.53 kg	0.1 kg
Dimensions	375 x 282 x 53 mm	Ø 38 x 165 mm
Supported languages	Polish, English	...
Manufacturer / Brand	BCS Line	AG TERMOPASTY
Guarantee	3 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00