

	IP CAMERA IPC-C22EP-A Wi-Fi CUE 2 - 1080p 2.8 mm IMOU	POE SWITCH / EXTENDER PFT1310 3-PORT	IP DECODER NVD0905DH-4I-4K - 12 Mpx, 4K
			
	24.35 USD 24.35 USD	20.41 USD 20.41 USD	4417.03 USD 4417.03 USD
Standard	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx
Resolution	1920 x 1080 - 1080p
Lens	2.8 mm
View angle	112 °
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af) 	...
Range of IR illumination	10 m
Management	...	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • Bi-directional audio streaming support
LED diodes	...	LAN, PoE	...
Transmission speed	...	10 / 100 Mbps	...
Image compression method	H.265 / H.264
Main stream frame rate	25 fps @ 1080p
Network protocols	TCP, DHCP
Supported resolutions	9 Channels @ 4000 x 3000 px - 12 Mpx , 9 Channels @ 3840 x 2160 px - 4K , 36 Channels @ 1920 x 1080 - 1080p , 81 Channels @ 1280 x 720 - 720p , 144 Channels @ 704 x 576 - D1
ONVIF	✓
Maximal output power	...	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade 	...
Number of supported screens	9 pcs

Main features	...	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender 	...
Video inputs	<ul style="list-style-type: none"> • 2 x HDMI 4K • 2 x DVI
WEB Server	—
Video outputs	9 x HDMI
Audio outputs	HDMI
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Network interface	Wi-Fi IEEE 802.11 b/g/n	...	2 x RJ45 10/100/1000 Base-T
Range	...	100 m - Input 100 m - Output	...
Default IP address	DHCP	...	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start	...	admin / -
Web browser access ports	—
Protections	...	Overvoltage	...
PC client access ports	—
Mobile client access ports	—
Housing	...	Plastic, DIN, TS-35 rail mounting	...
Port ONVIF	—
RTSP URL	—
Serial ports	<ul style="list-style-type: none"> • 2 pcs RS-232 @ RJ45 • 1 pcs RS-232 @ D-Sub • 1 pcs RS-485
Alarm inputs / outputs	4 / 4
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Operation temp. / Relative humidity	...	-30 ... 65 °C / 10 ... 90 %	...

Operation temp	-10 °C ... 55 °C
Main features	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection • Receive alarm notifications in the application when the camera detects motion • People detection • Audio detection • D-ZOOM - Digital Zoom : 16x
Power supply	5 V DC / 1 A - micro USB socket (power adapter included), Length of the cable : 2 m	PoE (802.3af/at)	230 V AC
Power consumption	< 3.1 W	0.3 W	≤ 70 W
Weight	0.1 kg	0.05 kg	4.70 kg
Dimensions	66 x 33 x 109 mm	79 x 52 x 23 mm	440 x 415 x 76 mm - 1.5 U
Supported languages	—
Manufacturer / Brand	DAHUA / IMOU	...	DAHUA
Guarantee	2 years	2 years	3 years