



	SWITCH POE GTX-C1-10-8G2G 8-PORT	UPS AT-UPS2000RT/2-RACK 2000 VA EAST
		
	87.62 EUR 87.62 EUR	659.58 EUR 659.58 EUR
Power adapter type	...	Online
Nominal power	...	1800 W
Apparent Power	...	2000 VA
Input voltage	...	230 V AC \pm 25 %
Input frequency	...	50 / 60 Hz (auto detection)
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Output voltage	...	230 V AC \pm 5 % (Pure Sine Wave)
Output frequency	...	50 / 60 Hz
Voltage adjustment	...	\pm 1 %
Frequency adjustment	...	—
Transfer time	...	4 ms
Management	—	...
Charging time (recover to 90% capacity)	...	3 hours
Battery	...	4 x 12V/9Ah
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed	...
Transmission speed	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Estimated battery operation time	...	<ul style="list-style-type: none"> • 55 minutes @ 200 W, • 27 minutes @ 400 W, • 12 minutes @ 600 W, • 10 minutes @ 800 W, • 7 minutes @ 1000 W, • 5 minutes @ 1200 W, • 2.5 minutes @ 1600 W

Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports 	...
Maximal total power	120 W	...
MAC addresses table	2k	...
Number of outputs	...	<ul style="list-style-type: none"> • 1 pcs CEE 7/3 (Schuko), • 2 pcs IEC-320 C13
Management software	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Certificates	CE, FCC Class B	...
Protections	Overvoltage \pm 4 kV	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch • Ethernet filter
Power supply	100 ... 265 V AC	...
Operation temp	-10 °C ... 45 °C	...
Operation state indication	...	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port
Application	...	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	...	Rack/Tower 2-in-1 Design

Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ~ 90 % (non-condensing)
Weight	0.79 kg	23.4 kg
Dimensions	210 x 150 x 35 mm	440 x 88 x 658 mm ; RACK 19", 2U
Manufacturer / Brand	...	EAST
Guarantee	2 years	2 years