





| | HANDLE FOR REMOTE CONTROL MC-755 MACLEAN | AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500C-0280B-S2 - 5 Mpx 2.8 mm DAHUA | INDUSTRIAL POE SWITCH PFS3228-24GT-360-V2 24-PORT SFP DAHUA | VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI |
|--|---|---|--|---|
| |  |  |  |  |
| | 5.94 EUR 5.94 EUR | 58.11 EUR 58.11 EUR | 332.89 EUR 332.89 EUR | 37.49 EUR 37.49 EUR |
| Max. width of the remote control | 47 mm | ... | ... | ... |
| Material | ABS | ... | ... | ... |
| Standard | ... | AHD, HD-CVI, HD-TVI, CVBS | ... | ... |
| Sensor | ... | 1/2.7 " CMOS | ... | ... |
| Standard | ... | ... | ... | <ul style="list-style-type: none"> • AHD - 4 Mpx • HD-CVI - 720p • CVBS - PAL / NTSC |
| Matrix size | ... | 5 Mpx | ... | ... |
| Number of inputs | ... | ... | ... | 1 pcs BNC |
| Number of outputs | ... | ... | ... | 1 pcs BNC |
| Input impedance | ... | ... | ... | 75 Ω |
| Output impedance | ... | ... | ... | 75 Ω |
| Galvanic (optical) isolation between signal inputs and outputs | ... | ... | ... | 1000 V peak |
| Opto-isolation between power and signal inputs / outputs | ... | ... | ... | 1000 V peak |
| Gain adjustment | ... | ... | ... | -3 dB ... +3 dB |
| Bandwidth | ... | ... | ... | 33 MHz / 1 Vpp |
| LAN ports | ... | ... | <ul style="list-style-type: none"> • 24 x RJ45 (2 Hi-PoE (802.3bt) + 22 PoE (802.3af/at) - 10/100/1000 Base-T), • 2 x Uplink (RJ45 - 10/100/1000 Base-T), • 2 x Uplink (port SFP - 1000 Base-X) | ... |
| Resolution | ... | 2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD-CVI only 960 x 576 - 960H | ... | ... |
| Lens | ... | 2.8 mm | ... | ... |
| View angle | ... | <ul style="list-style-type: none"> • 111 ° (manufacturer data) • 106 ° (our tests result) | ... | ... |
| Range of IR illumination | ... | 30 m | ... | ... |
| IR illuminator power adjustment | ... | Automatic | ... | ... |

| | | | | |
|-----------------------|---|---|---|------------------|
| Video output | ... | AHD / HD-CVI / HD-TVI / CVBS, 1 V _{pp} / 75 Ω | ... | ... |
| Transmission speed | ... | ... | <ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 24 x LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 x Uplink ports, • 1000 Mbps - 2 x SFP ports | ... |
| OSD menu | ... | ✓ | ... | ... |
| Management | ... | ... | — | ... |
| Maximal output power | ... | ... | <ul style="list-style-type: none"> • 30 W / port PoE • 90 W / port Hi-PoE | ... |
| Maximal total power | ... | ... | 360 W | ... |
| MAC addresses table | ... | ... | 8k | ... |
| Main features | ... | <ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance | ... | ... |
| Main features | <ul style="list-style-type: none"> • Built-in basis magnets allow mounting to metal surfaces • Aesthetic and solid construction • Very easy and quick assembly | ... | protection against lightning discharges and voltage differences and strokes between devices | ... |
| Power consumption | ... | ≤ 3.7 W | ... | ... |
| LED diodes | ... | ... | Power, Link/Act, PoE, System | ... |
| Housing | ... | Compact, Plastic | ... | ... |
| Certificates | ... | ... | CE | ... |
| Color | Black | White | ... | ... |
| "Index of Protection" | ... | IP67 | ... | ... |
| Power supply | ... | 12 V DC / 310 mA | 100 ... 240 V AC | 12 V DC / 90 mA |
| Operation temp | ... | -40 °C ... 60 °C | ... | ... |
| Operation temp | ... | ... | -10 °C ... 55 °C | ... |
| Weight | 0.03 kg | 0.18 kg | 3.44 kg | 0.088 kg |
| Dimensions | 110 x 55 x 27 mm | Ø 70 x 161 mm | 440 x 300 x 44 mm | 120 x 62 x 30 mm |
| Manufacturer / Brand | MACLEAN | DAHUA | DAHUA | DELTA |
| Guarantee | 2 years | 3 years | 5 years | 3 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00