

	SWITCH POE CS4006-4ET-60 4-PORT DAHUA	SWITCH POE CS4010-8ET-110 8-PORT DAHUA
		
	107.61 EUR 107.61 EUR	175.86 EUR 175.86 EUR
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports 	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports 	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power	60 W	110 W
MAC addresses table	8k	8k
Management	✓	✓
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes	Power, System, PoE, Link/Act	Power, System, PoE, Link/Act

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall
Certificates	CE	CE
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	Desktop, Metal	Desktop, Metal
Power supply	53 V DC / 1.22 A (power adapter included)	54 V DC / 2.22 A (power adapter included)
Power consumption	max. 65 W	max. 110 W
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.29 kg	0.49 kg
Dimensions	130 x 85 x 26 mm	190 x 106 x 30 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years