

|                              | <a href="#">EXTENDER VGA+AU/UTP</a>   | <a href="#">INSULATION STRIPPER HT-766</a>  | <a href="#">SMART ACTION TRIGGER INBOX/BLEBOX Wi-Fi CR123A</a>   | <a href="#">CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T</a>            |
|------------------------------|---|---|--|---|
|                              |    |  |    |  |
|                              | 63.27 EUR<br>63.27 EUR  | 6.34 EUR<br>6.34 EUR  | 22.68 EUR<br>22.68 EUR   | 29.85 EUR<br>29.85 EUR  |
| Material                     | ...   | Metal / PET   | ...  | ...   |
| Rated voltage                | ...   | ...   | 3 V - Battery type CR123A  | ...   |
| Tested cables                | ...   | ...   | ...  | UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)  |
| Maximal total load           | ...   | ...   | —  | ...   |
| Total maximal current        | ...   | ...   | —  | ...   |
| Number of inputs             | ...   | ...   | 4  | ...   |
| Number of outputs            | ...   | ...   | 0  | ...   |
| Application                  | ...   | Wire - 0.2 ... 6 mm <sup>2</sup> ( 24 AWG ... 10 AWG )                            | controlling devices, triggering actions  | ...   |
| Connector type               | ...   | ...   | Connection cube, screw terminals   | ...   |
| Wireless                     | ...   | ...   | Wi-Fi, 2.4 GHz - IEEE 802.11g  | ...   |
| Mobile phones support        | ...   | ...   | <ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul> | ...   |
| Housing                      | ...   | ...   | Plastic  | ...   |
| Device type                  | <b>Active / Transmitter</b><br><br><b>Active / Receiver</b>   | ...   | ...  | ...   |
| "Index of Protection"        | ...   | ...   | IP20   | ...   |
| Inputs                       | <ul style="list-style-type: none"> <li>• Video - VGA</li> <li>• Audio - stereo (Jack)</li> </ul> UTP  | ...   | ...  | ...   |
| Color                        | ...   | ...   | Black  | ...   |
| Outputs                      | <ul style="list-style-type: none"> <li>• Monitor - VGA</li> <li>• UTP</li> <li>• Audio - stereo (Jack)</li> <li>• Monitor - VGA</li> <li>• Audio - stereo (Jack)</li> </ul> | ...   | ...  | ...   |
| Power supply                 | 12 V DC / 1000 mA (power adapter included) 12 V DC / 1000 mA (power adapter included)   | ...   | ...  | 2 x 9V, type 6F22 battery (included)  |
| Video transmission range     | max. 140 m<br>max. 140 m  | ...   | ...  | ...   |
| Symmetrical socket impedance | 100 Ω<br>100 Ω  | ...   | ...  | ...   |

|                               |   |  |  |   |
|-------------------------------|---|--|--|---|
| Manufacturer / Brand          | ...   | ...  | BleBox   | UNI-T   |
| Connectors type               | <ul style="list-style-type: none"> <li>• 2 x VGA - Socket</li> <li>• 2 x Jack 3.5 mm socket</li> <li>• 1 x VGA Socket</li> <li>• 1 x Jack 3.5 mm socket</li> </ul>  | ...  | ...  | ...   |
| Symmetrical socket type       | RJ-45 (8-pin, 4 pairs) Socket<br>RJ-45 (8-pin, 4 pairs) Socket  | ...  | ...  | ...   |
| Weight                        | 0.2 kg<br>0.1 kg  | 0.35 kg  | 0.027 kg   | <ul style="list-style-type: none"> <li>• 0.11 kg - Transmitter</li> <li>• 0.14 kg - Receiver</li> </ul>   |
| Dimensions                    | 105 x 95 x 27 mm<br>72 x 46 x 24 mm   | 205 x 93 x 33 mm   | 35 x 33 x 23 mm  | <ul style="list-style-type: none"> <li>• 125 x 48 x 29 mm - Transmitter</li> <li>• 194 x 50 x 30 - Receiver</li> </ul>  |
| Main features                 | <ul style="list-style-type: none"> <li>• UTP cat. 5, 5e, 6</li> <li>• Signal correction</li> <li>• Metal housing</li> </ul>   | <ul style="list-style-type: none"> <li>• Breaking force adjustment knob,</li> <li>• Self-adjusting mechanism according to wire size provides excellent wire stripping without damaging the conductor,</li> <li>• Adjustable stop with lengths scale,</li> <li>• Cutter,</li> <li>• High durability tool, made from high quality materials</li> </ul> | <ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• µWiFi technology support,</li> <li>• Backup time : ~ 5 years</li> </ul> | <ul style="list-style-type: none"> <li>• Test for the presence of a short circuit, open circuit</li> <li>• Polarity indicator for telephone wire pairs : ± (5V ... 52V)</li> <li>• The maximum length of the telephone line : 3000 m</li> <li>• Optical - sound signaling</li> <li>• Low battery indicator</li> </ul> |
| Resolution                    | <ul style="list-style-type: none"> <li>• 1280 x 1024 px SXGA @ 60 m (manufacturer data)</li> <li>• 1024 x 768 px XGA @ 76 m (manufacturer data)</li> <li>• 800 x 600 px SVGA @ 106 m (manufacturer data)</li> <li>• 640 x 480 px VGA @ 137 m (manufacturer data)</li> <li>• 1920 x 1080 px Full HD @ 45 m (our tests result)</li> <li>• 1024 x 768 px XGA @ 100 m (our tests result)</li> </ul> | ...  | ...  | ...   |
| Bandwidth                     | ≤ 60 MHz DC   | ...  | ...  | ...   |
| Insertion loss                | < 3 dB  | ...  | ...  | ...   |
| Return loss                   | max. -15 dB   | ...  | ...  | ...   |
| Grounding                     | via grounding bolt  | ...  | ...  | ...   |
| Operation temp                | 0 °C ... 55 °C  | ...  | -20 °C ... 50 °C   | 0 °C ... 40 °C  |
| Permissible relative humidity | ≤ 95 %  | ...  | ...  | 20 % ... 75 %   |
| Guarantee                     | 2 years   | 2 years  | 2 years  | 2 years   |