


	COAXIAL CABLE RG-174 50 Ω	EXTENDER ETHERNET+PoE LR1002-1ET TRANSMITTER DAHUA	LITHIUM BATTERY BAT- CR1620 ENERGIZER
			
	0.40 USD 0.40 USD	56.78 USD 56.78 USD	1.13 USD 1.13 USD
Rated voltage	3 V
LAN ports	...	1 pcs RJ45	...
Transmission ports	...	1 pcs BNC	...
Type (size)	CR1620
Transmission speed	...	10 / 100 Mbps Full Duplex	...
In section	100 m . Price for 1m when buying a whole roll
Inner conductor	7 x Ø 0.16 mm Cu Stranded wire
Transmission range	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver	...
Protections	...	Overvoltage	...
Dielectric	Ø 1.6 mm PE full
Shield	—
Braid	64 x Ø 0.1 mm Stranded wire Cu
Impedance	50 Ω
Main features	...	<ul style="list-style-type: none"> • Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • The device operates from the camera side • Possibility to mount on a wall, or on the DIN TS-35 rail • UTP cable length to the camera max. 2 m 	...

Outer coating	Ø 2.8 mm PVC
Power supply	...	<ul style="list-style-type: none"> • ePoE • PoE (802.3af/at) 	...
Weight	...	0.061 kg	0.001 kg
Dimensions	...	79 x 64 x 23 mm	Ø 15.9 x 2.0 mm
Manufacturer / Brand	...	DAHUA	ENERGIZER
Cable attenuation at 100m section	17.6 dB @ 30 MHz 21.1 dB @ 50 MHz 28.2 dB @ 100 MHz 21.6 dB @ 146 MHz 80 dB @ 440 MHz 96 dB @ 1000 MHz 240 dB @ 2400 MHz
Guarantee	2 years	3 years	2 years

