



	IP CAMERA IPC-HFW2249S-S-IL-0280B WizSense - 1080p 2.8 mm DAHUA	EXPANSION PLUG KW-10/6X60 KLIMAS
		
	2164.81 NOK 2164.81 NOK	1.88 NOK 1.88 NOK
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Material	...	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Drilling diameter	...	10 mm
Expansion plug length	...	60 mm
Screw dimensions	...	Ø 6 x 60 mm, PZ-3
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Scanning system	Progressive	...
Application	...	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 101 ° (our tests result) 	...
Range of IR illumination	30 m	...
White light LED illuminator range	30 m	...
Min. illumination	0.002 Lux / F1.0 (color)	...
S/N ratio	> 56 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio detection 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	21.06	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...

Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles video tampering 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 330 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 3.9 W @ 12 V DC • ≤ 4.4 W @ PoE 	...
Housing	Compact - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.47 kg	...
Dimensions	162 x 70 x 70 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	DAHUA	KLIMAS
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00