




| | ACCESS CONTROLLER PR102DR | EXTENSION CABLE DC-2.1/5.5-WG-10M 10 m | ACCESS POINT 4G LTE +ROUTER RUT901 Dual SIM 2.4 GHz 300 Mbps Teltonika |
|------------------------|---|---|--|
| |  |  |  |
| | 74.60 GBP 74.60 GBP | 5.11 GBP 5.11 GBP | 114.25 GBP 114.25 GBP |
| Frequency range | ... | ... | 2.4 GHz |
| Environment class | I | ... | ... |
| Relay contacts load | 1.5 A / 30 V | ... | ... |
| Battery backup support | — | ... | ... |
| Input lines | 2 | ... | ... |
| Connector type | ... | 1 x Ø 2.1/5.5 mm Straight socket 1 x Ø 2.1/5.5 mm Straight plug | ... |
| Antenna type | ... | ... | 2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector) |
| Output lines | 2 | ... | ... |
| Length of the cable | ... | 10 m | ... |
| Rated voltage | ... | 12 V DC | ... |
| Communication | • RS-485 • RACS (Roger) | ... | ... |
| Color | ... | Black | ... |
| Standards | ... | ... | IEEE 802.11 b/g/n, 4G, 3G, 2G |
| Baud rates | ... | ... | 11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.236 Mbps (4G / 3G / 2G) |
| LAN ports | ... | ... | • 1 x 10/100 Mbps - WAN • 3 x 10/100 Mbps - LAN |
| Transmitter power | ... | ... | ≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM |
| LED indicators | ... | ... | Power, WAN, 3 x LAN, LTE, Signal indicator |
| Network type | ... | ... | 4G, 3G |
| LTE | ... | ... | ✓ |
| QSS | ... | ... | — |

| | | | |
|-------------------------------|---|----------|--|
| WDS | ... | ... | — |
| DHCP server | ... | ... | ✓ |
| Protections | ... | ... | <ul style="list-style-type: none"> • WPA-PSK/WPA2-PSK • WPA2-PSK • WPA2-EAP • WPA2-EAP/WPA3-EAP • WPA3-EAP • WPA2-PSK/WPA3-SAE • WPA3-SAE • OWE • AES-CCMP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering |
| Management interface | ... | ... | Web browser, Teltonika RMS application, SMS |
| Main features | <ul style="list-style-type: none"> • PRT series readers support • DIN, TS-35 rail mounting • 4000 indexed users • History of 32000 events • Real-time clock and calendar • Remote programming from PC | ... | <ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • 2 x SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems |
| Power supply | 10 ... 15 V DC | ... | <ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 |
| Power consumption | ... | ... | ≤ 7 W |
| Operation temp | 5 °C ... 40 °C | ... | -40 °C ... 75 °C |
| Permissible relative humidity | 10 ... 95 % (non-condensing) | ... | 10 % ... 90 % (non-condensing) |
| Weight | 0.13 kg | 0.245 kg | 0.26 kg |
| Dimensions | 98 x 88 x 73 mm | ... | 110 x 100 x 50 mm |
| Manufacturer / Brand | ROGER | ... | Teltonika |
| Guarantee | 2 years | 2 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00