



	IP VANDALPROOF CAMERA DS-2CD2123G2-IS(2.8MM)(D) - 1080p Hikvision	IP CAMERA APTI-W31C2-TUYA-V2 Wi-Fi - 3 Mpx 3.6 mm
		
	194.62 GBP 194.62 GBP	26.18 GBP 26.18 GBP
Standard	TCP/IP	IP
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Scanning system	Progressive	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p	2048 x 1536 - 3 Mpx
Lens	2.8 mm	3.6 mm
View angle	107 °	95 °
Range of IR illumination	30 m	30 m
RS-485 interface	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	Smart H.264
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input, • Audio output, • Bi-directional audio streaming support 	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support
Main stream frame rate	25 fps @ 2 Mpx	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 128GB support (possible local recording)
Network interface	10/100 Base-T (RJ-45)	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n • 100 Base-T
WEB Server	Built-in	—
Max. number of on-line users	6	...
ONVIF	✓	—
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	Access by a cloud (P2P) <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	DHCP
Web browser access ports	80	—

PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	—
Mobile client access ports	8000	—
Port ONVIF	80	—
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	—
Operation temp	...	-20 °C ... 55 °C
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Mirror - Mirror image • Motion Detection - classification of people and vehicles • Configurable Privacy Zones • Possibility to change the resolution, quality and bit rate • RESET button • Sharpness - sharper image outlines • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, face detection 	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 30 m (open area) • Video PUSH personal messaging • Motion Detection • Sound signaling • ICR - Movable InfraRed filter • RESET button
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	12 V DC / 670 mA (power adapter included)
Power consumption	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC 	≤ 8 W
Housing	Dome, Metal	Metal
Vandal-proof	IK10	...
"Index of Protection"	IP67	IP66
Color	White	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.55 kg	0.333 kg
Dimensions	Ø 111 x 85 mm	195 x 62 x 62 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	English
Manufacturer / Brand	Hikvision	APTI

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

SAP Code	311319893	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00