







	AUXILIARY CONTACT LE-406250 FOR THE LEGRAND DEVICES OF THE TX3, DX3, FR300, FRX300, FRX400 SERIES LEGRAND	POWER CORD CABLE CEE-716/IEC-C7 1.6 m	FINGERPRINT READER MODULE VTO4202F-MF FOR MODULE VTO4202F-P DAHUA	VIDEO DOORPHONE VTO2101E-P-S2 DAHUA	MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD	SMART CONTROLLER FOR ROLLER SHUTTERS M/SRW-01 Wi-Fi 230 V AC ZAMEL
						
	153.99 SEK 153.99 SEK	17.09 SEK 17.09 SEK	1890.01 SEK 1890.01 SEK	3844.22 SEK 3844.22 SEK	115.80 SEK 115.80 SEK	927.00 SEK 927.00 SEK
Device type	Auxiliary contact
Support	SUPLA
Compatibility	VTO4202F-P	DAHUA
Application	roller shutters, roof windows, awnings, drop-down screens, curtains
Number of pins	1
Number of inputs	2 pcs
Total maximal current	10 A	...
Sensor	1/2.8", 2.1 Mpx CMOS
Contact type	NO/NC
Maximal total load	2300 W	...
Cable	...	IEC320 C7 Socket / Power connector
Lens	3.6 mm
Connectors type	screw terminals
Response time	< 25 ns	...
Length of the cable	...	1.6 m
View angle	80 °
Number of outputs	1 pcs (Motor)
Number of outlets	2 grounded outlets 10A/250V	...
Voltage	...	max. 250 V
Image compression method	H.265 / H.264
Rated voltage	230 V AC	230 V AC / 50 Hz	230 V AC
Current	...	—
LED illuminator	—
Relay maximal load	250 V AC / 6 A	5 A
Maximal voltage	250 V / 50 Hz	...
IR illuminator	✓
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Maximal outputs load	350 W
Connector type	screw terminals
Nominal stroke current	2 kA (L/N) - (8/20µs)	...
Width in 17.5 mm modules	0.5
Vandal-proof	IK07
Maximum stroke current	10 kA (L/N) - (8/20µs)	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Electric shock protection system	Ground connectors (pins) connected with ground wire of AC mains	...
Permissible relative humidity	10 ... 90 % (non-condensing)

Main features	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Solid workmanship 	Support up to 3000 finger prints	<ul style="list-style-type: none"> • It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH1 / VTH2 / VTH5 indoor panel • Doorbell button, • Lock control, • Bidirectional communication, • Microphone built-in, • Speaker built-in, • Noise and echo reduction • Tamper detection - removing from mounting surface • RS-485 interface • Alarm inputs - 1 pcs • Video PUSH personal messaging • Voice message • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter 	...	<ul style="list-style-type: none"> • Local control by physical button • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API
Mobile phones support	<ul style="list-style-type: none"> Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • IOS (iPhone): Free application DMSS 	...	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS
Power supply	5 V DC - Supplied from other modules	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1 A, - DAHUA
Power consumption	< 1 W	<ul style="list-style-type: none"> ≤ 5 W (operation) ≤ 2.5 W (Standby mode)
Supported languages	English
Housing	Plastic, Direct mounting on selected Legrand DIN TS-35 rail mounting units, on the left-hand side of the device	...	Metal + Plastic, Waterproof	Metal - Zinc alloy, Waterproof - IK10	Plastic - non-flammable	Plastic
Color	Silver	Graphite	...	Green
"Index of Protection"	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	IP65	...	IP20
Operation temp	-20 °C ... 60 °C	-40 °C ... 60 °C	...	-10 °C ... 55 °C
Weight	0.034 kg	0.084 kg	0.21 kg	0.67 kg	0.12 kg	0.030 kg
Dimensions	9 x 85 x 78 mm	...	100 x 100 x 38.5 mm	73 x 163 x 55 mm	131 x 55 x 75 mm	40 x 38 x 17 mm
Manufacturer / Brand	LEGRAND	...	DAHUA	DAHUA	...	ZAMEL
Guarantee	2 years	2 years	3 years	3 years	2 years	2 years