

	<a href="#">OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND</a>	<a href="#">TV OR MONITOR MOUNT AX-TYTAN-ALUXX</a>	<a href="#">EXPANSION PLUG KW-10/5X50 KLIMAS</a>	<a href="#">EXPANSION PLUG KW-8/5X80 KLIMAS</a>	<a href="#">BATTERY 12V/26AH-VPRO</a>
					
	219.49 EUR 219.49 EUR	105.41 EUR 105.41 EUR	0.10 EUR 0.10 EUR	0.15 EUR 0.15 EUR	56.31 EUR 56.31 EUR
Battery capacity	...	...	...	...	26 Ah
Device type	Overvoltage limiter, Three-phase	...	...	...	...
Battery charging current	...	...	...	...	max. 7.8 A
Connector	...	...	...	...	M5 screw
Material	...	...	<ul style="list-style-type: none"> <li>Expansion plug, Polypropylene</li> <li>Screw, Steel galvanized</li> </ul>	<ul style="list-style-type: none"> <li>Expansion plug, Polypropylene</li> <li>Screw, Steel galvanized</li> </ul>	...
Drilling diameter	...	...	10 mm	8 mm	...
Rated voltage	230 / 400 V AC, 50 / 60 Hz	...	...	...	12 V
Battery type	...	...	...	...	Maintenance-free AGM (Absorbent Glass Mat) battery
Expansion plug length	...	...	50 mm	50 mm	...
Mounting standard	...	VESA : 200, 300, 400 x 200, 400, 600 x 400	...	...	...
Maximal voltage	320 V AC, 50 / 60 Hz	...	...	...	...
Battery lifetime	...	...	...	...	8 ... 10 years
Screen size range	...	37 " ... 70 "	...	...	...
Screw dimensions	...	...	Ø 5 x 50 mm, PZ-2	Ø 5 x 80 mm, PZ-2	...
Bearing capacity	...	45 kg	...	...	...
Class	1+2 type ( Class B+C )	...	...	...	...
Distance from mounting surface	...	54 ... 448 mm	...	...	...
Application	...	...	<ul style="list-style-type: none"> <li>Concrete</li> <li>Solid clay brick</li> <li>Solid sand-lime brick</li> </ul>	<ul style="list-style-type: none"> <li>Concrete</li> <li>Solid clay brick</li> <li>Solid sand-lime brick</li> </ul>	...
Color	...	Silver / Black	...	...	...
Protection level Up L/PE, N/PE	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)	...	...	...	...
Tilt adjustment	...	-15 ° ... 15 °	...	...	...
Horizontal rotation	...	-60 ° ... 60 °	...	...	...
Rotation in the plane of the screen	...	± 3 °	...	...	...
Nominal discharge current (L/PE, N/PE)	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)	...	...	...	...
Maximum stroke current (L/N, L/PE, N/PE)	50 kA @ 8/20 µs (T2)	...	...	...	...
Operation state indication	✓	...	...	...	...
Connectors type	screw terminals	...	...	...	...
Housing	Plastic, DIN, TS-35 rail mounting	...	...	...	...
Width in 17.5 mm modules	4	...	...	...	...
Weight	0.552 kg	4.76 kg	...	...	7.12 kg
Dimensions	71 x 83 x 70 mm	720 x 435 x (54 ... 448) mm	...	...	175 x 125 x 166 mm
Manufacturer / Brand	LEGRAND	...	KLIMAS	KLIMAS	V-PRO
Guarantee	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00