



	<a href="#">NVR NVR304-32X 32 CHANNELS UNIVIEW</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-LCD-142A</a>
		
	1615.78 EUR 1615.78 EUR	15.87 EUR 15.87 EUR
Standard	TCP/IP	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
Mounting standard	...	VESA 75, 100, 150, 200, 200x100
Video outputs	2 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output	...
Screen size range	...	17 " ... 37 "
Bearing capacity	...	20 kg
Audio support	<ul style="list-style-type: none"> <li>• 32 Channels - Audio from cameras</li> <li>• Bi-directional audio streaming support</li> </ul>	...
Audio inputs	1 pcs CINCH	...
Distance from mounting surface	...	70 ... 250 mm from wall
Audio outputs	1 pcs CINCH	...
Color	...	Black
Tilt adjustment	...	-15 ° ... 15 °
Image compression method	Ultra 265 / H.265 / H.264	...
Bitrate	max. 384 Mbps	...
Horizontal rotation	...	Articulated arm with two swivels in range -90 ° ... 90 ° each
Rotation in the plane of the screen	...	360 °
Supported hard drives	4 x 10 TB SATA + 1 x eSATA Possibility of operation the disks in RAID 1/5 array	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...

Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9/16/25/36 channel synchronous playback	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...
Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS	...
ONVIF	✓	...
Default IP address	DHCP or 192.168.1.30	...
Default admin user / password	admin / 123456	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...
Mobile client access ports	80	...
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream	...
USB	2 x USB 2.0 1 x USB 3.0	...
Serial ports	RS-485, RS-232	...
Alarm inputs / outputs	16 / 4	...
PTZ control	• PTZ Uniview cameras • RS-485 - PELCO-D/P and others	...
Motion Detection	✓	...
Intelligent image analysis	✓	...

Main features	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, people counting, crowd gathering estimation, scene changing, objects tracking</li> <li>• Smoke and temperature detection, fire detection</li> <li>• Audio detection</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Fisheye-Dewarping - correction of the "fish eye" view to the perspective view</li> <li>• VIDEO signal loss alarm</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> </ul>	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	100 ... 240 V AC	...
Power consumption	max. 25 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	5.2 kg	1.1 kg
Dimensions	442 x 426 x 89 mm	195 x 119 x (70 ... 250) mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years