



	<a href="#">IP CAMERA DS-2CD1347G2H-LIU(2.8MM) Smart Hybrid Light - 4 Mpx Hikvision</a>	<a href="#">ACCESS CONTROL PANEL ACCO-NT2 SATEL</a>
		
	2269.48 NOK 2269.48 NOK	4275.52 NOK 4275.52 NOK
Standard	IP	...
Inputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>
Outputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>
Resolution	2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Sensor	1/3 " Progressive Scan CMOS	...
Communication	...	<ul style="list-style-type: none"> <li>• 2 x RS-485</li> <li>• Expander bus - up to 32 expander modules</li> </ul>
Lens	2.8 mm	...
View angle	96 °	...
White light LED illuminator range	30 m	...
Events memory	...	<ul style="list-style-type: none"> <li>• Events saving to the micro SD card (included)</li> <li>• Recording up to 1 000 000 events from the control panel,</li> <li>• Max. 100 000 events read from each access control module</li> </ul>
Range of IR illumination	30 m	...
Memory card slot	—	...
Users + admins	...	<ul style="list-style-type: none"> <li>• 8000 + 1</li> <li>• Max. 65 000 users in the whole ACCO NET system</li> </ul>
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Noise and echo reduction</li> </ul>	...
Output load	...	<ul style="list-style-type: none"> <li>• OC : 50 mA / 12 V DC</li> <li>• +EX : 0.5 A / 12 V DC</li> <li>• AUX : 0.5 A / 12 V DC</li> </ul>
Main stream frame rate	20 fps @ 4 Mpx 25 fps @ 1080p	...
Interface	10/100 Base-T (RJ-45)	...

WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Main features	...	<ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul>
Battery backup support	...	—
Operation temp	...	-10 °C ... 55 °C
Permissible relative humidity	...	93 % (non-condensing)



Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> </ul>	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>	12 V DC / 140 mA (max)
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 7.5 W @ PoE</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>	...
Housing	Dome, Metal + Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.39 kg	0.096 kg
Dimensions	Ø 110 x 93 mm	151 x 69 x 17 mm
Supported languages	English, Ukrainian	...
Manufacturer / Brand	Hikvision	SATEL
SAP Code	311325148	...
Guarantee	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00