










	EXPANSION PLUG KW-10/6X100.KLIMAS	CABLE 2C-W/2C-G-3.0M 3 m	LAMINATED PVC CARD ATLO-100	WIRED DOORBELL ATLO: DB-1	EXTENDER HDMI+USB: EX-100-4K	ALKALINE BATTERY BAT: LR43/P2 ENERGIZER	EXTENDER HDMI: EX-120-4K-V4	POWER DISTRIBUTION UNIT ACAR-DIGITAL (5 OUTLETS)
								
	0.25 EUR 0.25 EUR	1.11 EUR 1.11 EUR	0.17 EUR 0.17 EUR	4.07 EUR 4.07 EUR	205.32 EUR 205.32 EUR	1.02 EUR 1.02 EUR	178.54 EUR 178.54 EUR	55.88 EUR 55.88 EUR
Standard	---
Supported HDMI standard	1.4	...
Listen to the available sounds	
HDCP	1.4	...
Signaling mode	Sound signaling
Protection level	≤ 1.3 kV
Protocols	HDbiT	...
Number of ring-tones	1
In package	2 pcs The price for package
Nominal load current	10 A (total)
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized
Volume adjustment	---
Rated voltage	1.5 V	...	230 V AC / 50 Hz
Maximal load power	2300 W
Drilling diameter	10 mm
Cable	...	2 x CINCH Plug / 2 x CINCH Socket
Expansion plug length	60 mm
"Index of Protection"	IP40
Type (size)	LR43 / 186
Nominal stroke current	2 kA (L/N) - 8/20 μs
Maximum stroke current	6.5 kA (L/N) - 8/20 μs
Screw dimensions	Ø 6 x 100 mm, PZ-3
Leak current	< 0.5 mA
Automatic delayed fuse	✓
Response time	< 25 ns
Application	• Concrete • Solid clay brick • Solid sand-lime brick
Manufacturer / Brand	KLIMAS	...	ATLO	ATLO	...	ENERGIZER
Number of outlets	5 grounded outlets 16A/250V - (Schuko)
Switch	Two-way switch - with light indication
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD	...	• 480i @ 60Hz, • 480p @ 60Hz, • 576i @ 50Hz, • 576p @ 50Hz, • 720p @ 50/60Hz, • 1080i @ 50/60Hz, • 1080p @ 50/60Hz, • 4K UHD @ 24/25/30Hz	...
Maximal transmission range	• 70 m UTP cat. 6 @ 4K UHD. • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result)	...	• 80 m UTP cat. 5 • 100 m UTP cat. 5e • 120 m UTP cat. 6	...
Permissible relative humidity	0 % ... 90 % (non- condensing)
Main features	...	• Very easy and quick assembly	• Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output	...	• IR carrier frequency : 20 kHz ... 60 kHz • Protections : lightning, Overvoltage, ESD	...
Power supply	12 V DC	• Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included)	...	5 V DC / 2 A (2 pcs of power supply adapters included)	...
Main features	• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse	• Easily readable LCD with backlight displaying detailed information on system state, • Supply voltage measurement : 80 V ... 250 V @ 50Hz, • Supply current measurement : 0.01 A ... 10 A @ 50/60 Hz, • Power measurement : 1 W ... 2500 W, • Energy measurement : 1 Wh ... 9999 Wh • Energy meter reset • Setting the alarm after exceeding the power consumption
Current consumption	• 4 W Receiver • 6 W Transmitter	...
Length of the cable	...	3 m	3 m

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	Plastic - non-flammable
Operation temp	-20 °C ... 60 °C	..	0 °C ... 60 °C	..
Weight	..	0.073 kg	0.006 kg	0.06 kg	0.29 kg	0.001 kg	..	0.65 kg
Transmitter and receiver weight	0.33 kg	..
Dimensions	86 x 54 x 1 mm	62 x 88 x 24 mm	150 x 107 x 28 mm - Transmitter or receiver dimensions	Ø 11.6 x 4.2 mm	113 x 95 x 24 mm	447 x 57 x 43 mm
Guarantee	2 years	2 years	2 years	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00