





	<a href="#">RUBBER MAT MB-GUM/50</a>	<a href="#">ACCESS CONTROLLER ASC3202B DAHUA</a>	<a href="#">SOLDERING PASTE AGT-038 AG TERMO PASTY</a>
			
	46.61 DKK 46.61 DKK	3727.39 DKK 3727.39 DKK	16.19 DKK 16.19 DKK
Package	...	...	Can
Number of served transitions	...	2	...
Flux marking in accordance with DIN EN 29454-1	...	...	1.1.2.C
Support	...	Cooperation with the access control systems	...
Type of flux	...	...	rosin based
Application	<ul style="list-style-type: none"> <li>• Area covering,</li> <li>• Soundproofing</li> </ul>	...	...
Kind of flux	...	...	halide, RMA
Form of flux	...	...	Paste
Number of supported readers	...	<ul style="list-style-type: none"> <li>• 2 pcs RS-485,</li> <li>• 2 pcs Wiegand</li> </ul>	...
Material	SBR granulate + polyurethane binder	...	...
Battery backup support	...	—	...
Flash point	...	...	> 150 °C
Alarm inputs / outputs	...	2 / 2	...
Density	...	...	~ 1.1 g/cm <sup>3</sup> @ 80 °C
Flux solubility	...	...	Not dissolved in water
Communication	...	<ul style="list-style-type: none"> <li>• 3 x RS-485,</li> <li>• 2 x Wiegand 34/26,</li> <li>• 1 x Ethernet 10 / 100 Mbps (RJ-45)</li> </ul>	...
Network protocols	...	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Main control mode</li> <li>• Sub control mode</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• Rough structure</li> <li>• Granule fraction : 0.5 ... 4 mm</li> <li>• Insulation</li> <li>• High fatigue strength of the material</li> <li>• Weatherproof</li> <li>• Very easy and quick assembly</li> </ul>	<ul style="list-style-type: none"> <li>• Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control)</li> <li>• 1000 indexed users</li> <li>• Support up to 3000 finger prints</li> <li>• Memory of 5000 RFID cards</li> <li>• Support storage of 300 000 records</li> <li>• 128 General Purpose Schedules</li> <li>• Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above</li> <li>• Tamper protections</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Beep signal - Buzzer</li> <li>• White list, Black list</li> <li>• Web-Server built-in</li> <li>• Software update via network</li> <li>• Monitoring and configuration through network - SmartPSS Lite application</li> <li>• Power output 12 V DC / 1 A - supplying power to the lock</li> <li>• Support hardware I/O port configuration and export configuration diagrams</li> <li>• ONVIF compliance</li> </ul>	...
Power supply	...	<ul style="list-style-type: none"> <li>• 12 V DC / 2.5 A</li> <li>• PoE (802.3at)</li> </ul>	...
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 2 W (standby)</li> <li>• max. 20.4 W @ 12 V (operation)</li> <li>• max. 14.4 W @ PoE (operation)</li> </ul>	...
Housing	...	Plastic (PC + ABS)	...
Color	Black	White	Light brown

IK rating	...	IK06	...
Operation temp	...	-10 °C ... 55 °C	> 350 °C
Permissible relative humidity	...	5 % ... 95 % (non-condensing)	...
Weight	2.4 kg	0.72 kg	100 g
Dimensions	500 x 500 x 10 mm	186 x 186 x 58 mm	...
Manufacturer / Brand	...	DAHUA	AG TERMOPASTY
Guarantee	...	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00