




	<a href="#">MASKING PLATE CDN-M-S ACO</a>	<a href="#">HOUSING BRACKET BR-300TP</a>	<a href="#">IP CAMERA IPC-HDW3549H-AS-PV-0280B-S4 TiOC Full-Color - 5 Mpx 2.8 mm DAHUA</a>
			
	21.57 EUR 21.57 EUR	9.92 EUR 9.92 EUR	421.39 EUR 421.39 EUR
Material	...	Aluminum	...
Standard	...	...	TCP/IP
Distance from mounting surface	...	285 mm	...
Sensor	...	...	1/2.7 " Progressive Scan CMOS
Cable hiding	...	—	...
Matrix size	...	...	5 Mpx
Compatibility	CDN-R-S, CDN-R2-S	...	...
Material	Stainless steel	...	...
Adjustment	...	in two planes	...
Plate thickness	1.5 mm	...	...
Internal dimensions	212 x 94 mm	...	...
External dimensions	252 x 230 mm	...	...
Resolution	...	...	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	...	...	2.8 mm
View angle	...	...	• 97 ° (manufacturer data) • 105 ° (our tests result)
Range of IR illumination	...	...	≤ 30 m
White light LED illuminator range	...	...	≤ 30 m
Min. illumination	...	...	0.003 Lux / F1.0 ( Color, 30IRE )
Image compression method	...	...	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264 / H.264H / H.264B / MJPEG
Memory card slot	...	...	Micro SD memory cards up to 256GB support (possible local recording)
RS-485 interface	...	...	—
Alarm inputs / outputs	...	...	1 / 1
Audio	...	...	• Microphone built-in : 2 pcs • Audio input, • Audio output, • Speaker built-in, • Bi-directional audio streaming support, • Audio detection, • Compliance with the AAC standard
Main stream frame rate	...	...	20 fps @ 5 Mpx 25 fps @ 4 Mpx
Network interface	...	...	10/100 Base-T (RJ-45)
Network protocols	...	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP
WEB Server	...	...	Built-in
Max. number of on-line users	...	...	20
ONVIF	...	...	21.12

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	...	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Default IP address	...	...	192.168.1.108
Default admin user / password	...	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	...	80, 37777
PC client access ports	...	...	37777
Mobile client access ports	...	...	37777
Port ONVIF	...	...	80
RTSP URL	...	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Full Color - colorful night mode</li> <li>• White light (LED) illuminator built-in</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Light and sound alarm</li> <li>• Active deterrence function</li> <li>• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms</li> <li>• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles</li> <li>• AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters</li> <li>• IVS analysis : Smart motion detection (with recognizing people and vehicles), crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, video tampering</li> </ul>
Housing	...	...	Dome - Metal
Color	Silver	White	White
"Index of Protection"	...	...	IP67
Vandal-proof	...	...	—
Power supply	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 770 mA</li> </ul>
Power consumption	...	...	<ul style="list-style-type: none"> <li>• ≤ 8.8 W @ PoE</li> <li>• ≤ 8.3 W @ 12 V</li> </ul>
Operation temp	...	...	-40 °C ... 60 °C
Weight	0.450 kg	0.45 kg	0.75 kg
Dimensions	...	...	Ø 122 x 111 mm
Supported languages	...	...	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	ACO	...	DAHUA
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00