



	VOLTAGE CONVERTER MOD-DC-12V ACO	ACCESS CONTROLLER MODULE MC16-PAC-EX-2 ROGER
		
	24.54 AUD 24.54 AUD	831.64 AUD 831.64 AUD
Type	Decreasing the voltage	...
Number of served transitions	...	2
Inputs	...	12
Power voltage	14 V ... 16 V DC	...
Outputs	...	8
Output voltage	12 V DC	...
Output current	0.5 A (max)	...
Number of users	...	max. 12000 - Number of identifiers
Power	6 W (max)	...
Application	reversible electric door strikes	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Number of permissions per ID	...	100
Buffer memory	...	8 000 000 events buffer
Protections	<ul style="list-style-type: none"> • Overheat • Overload • Short-circuit 	...
MCT readers support	...	16 pcs
Readers connections	...	4 pcs - Wiegand / PRT
Number of login points	...	4
Number of access terminals	...	8
Number of access zones	...	4
Number of alarm zones	...	4
Number of automation nodes	...	4
Battery backup support	...	12 V / 7 Ah
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)

Main features	...	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.018 kg	0.14 kg
Dimensions	54 x 31 x 15 mm	175 x 72 x 30 mm
Manufacturer / Brand	ACO	ROGER
Guarantee	2 years	3 years