

	MULTISWITCH TMS-9/6-9 INPUTS:6 OUTPUTS:TRIAx	SWITCHING ADAPTER 24V/1.5AGPV	SET OF UTP / COAXIAL CONVERTERS FOR LAN+PoE TRANSMISSION XC0AX4-SET 2 PCS SET ATE	EXTENDER HDMI PEM700- E DAHUA	EXTENDER HDMI+USB- EX-70-4K2	SLEEVE AND EXPANSION ANCHORS KM-M10X80*P4	EXTENSION CABLE DC-2.1/5.5-WG-10M_10 m	ELECTRIC CABLE YKY-3X2.5	POWER DISTRIBUTION UNIT LE-04942 (5 OUTLETS) 3 m LEGRAND
									
	74.33 EUR 74.33 EUR	10.67 EUR 10.67 EUR	113.77 EUR 113.77 EUR	201.83 EUR 201.83 EUR	178.15 EUR 178.15 EUR	1.16 EUR 1.16 EUR	6.06 EUR 6.06 EUR	1.37 EUR 1.37 EUR	20.98 EUR 20.98 EUR
Adapter type	...	Switching
Connectors	• 1 pcs RJ45 • 1 pcs cable terminal • 1 pcs BNC
Power voltage	...	90 ... 264 V AC
Total maximal current	16 A
In package	4 pcs The price for package
In section	100 m - Price for 1m when buying a whole roll	...
Maximal total load	3680 W
LAN ports	1 pcs RJ45 100 Mbps
Frequency range	...	47 ... 63 Hz
Screw	M10 x 80 mm
Output voltage	...	24 V DC
Connector type	1 x Ø 2.1/5.5 mm Straight socket 1 x Ø 2.1/5.5 mm Straight plug
Inputs	8x 950 MHz ... 2150 MHz 1x 47 MHz ... 862 MHz
Number of outlets	5 grounded outlets 16A/250V CEE 7/5
Supported HDMI resolutions	1080p, 1080i, 720p, 576p, 576i, 480p, 480i	max. 4K UHD @ 60 Hz
Drilling diameter	14 mm
Inner conductor	3 x 2.5 mm ² - Cu wire	...
Output voltage tolerance	...	± 3 %
Fuse
Switch
Screw threading length	36 mm
Rated voltage	12 V DC	0.6 / 1 kV	230 V AC / 50 Hz
Maximal load	...	1.5 A
Wire gauge	3 x 1.5 mm ²
Sleeve diameter	13.5 mm
Output power	...	36 W
Outputs	6x 47 MHz ... 2150 MHz
Length of the cable	10 m	...	3 m
Sieve length	53 mm
Outer coating	Ø 10 mm - PVC	...
Efficiency	...	84 %
HDMI standard	1.3
Material	Steel galvanized
Coating color	Black	...
Number of outputs	...	1 pcs
Color	Black	White / Gray
Application	Concrete, Solid clay brick
Switching signals	13 V / 18 V 0 Hz / 22 kHz
SAT amplification (cable pre-correction)	...	2 dB
TV Tap loss	2 dB
Maximal output level SAT	100 dBpV
Maximal output level TV	85 dBpV
Maximal transmission range	60 m (max) @ 720p / 1080p - UTP cat. 5e, 6	• 60 m - UTP cat. 6, 6A, 7 @ 4K UHD (manufacturer data) • 70 m - UTP cat. 5e @ 1080p (our tests result) • 20 m - UTP cat. 5e @ 4K UHD (our tests result) • 60 m - UTP cat. 6 @ 4K UHD (our tests result)	
Housing type	...	Plastic, Waterproof
Main features	• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Support KVM function, • HDR10 support • Transition of the HDMI signal in the transmitter • EDID support • ESD protection
LAN+PoE port configuration description	• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3af) ≤ 15 W (*+/-: 1, 2 pins; +/:-: 3, 6 pins) or (*+/-: 4, 5 pins; +/:-: 7, 8 pins) • xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3af) ≤ 30 W, PoE (802.3af) ≤ 15 W
Transmission range	< 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera
Permissible relative humidity	0 % ... 95 %	0 % ... 90 % (non-condensing)
LED indicators	• PoE • LAN • Link • 10Mb

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	...	<ul style="list-style-type: none"> • Overload • Short-circuit • Overvoltage 	<ul style="list-style-type: none"> • Overvoltage - LAN, BNC • Short-circuit - xCOAX4-SW
Main features	...	<ul style="list-style-type: none"> • Protection class : II • Box casing designed to wall mounting 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Watchdog function - Coaxial cable 	<ul style="list-style-type: none"> • IR receiver • An additional HDMI output in transmitter module • The distance switch (EO) settings cause the initial signal correction • EDID support 	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression, • No delays in video transmission, • No delays in mouse control operations • Designed to continuous operation 24/7
Power supply	<ul style="list-style-type: none"> xCOAX4-SW : <ul style="list-style-type: none"> • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage 	5 V DC / 1000 mA (power adapter included) - TX side	5 V DC / 1 A - 2 pcs (included)
Power consumption	1.35 W (total)
Housing	Plastic (PC)	Plastic
"Index of Protection"	...	IP67	IP20
Operation temp	...	-20 °C ... 70 °C	-25 °C ... 65 °C	-10 °C ... 55 °C	-20 °C ... 60 °C
Weight	...	0.22 kg	0.033 kg (single element)	0.134 kg	0.12 kg	0.245 kg	0.57 kg
Dimensions	359 x 103 x 71 mm	148 x 32 x 28 mm	<ul style="list-style-type: none"> • 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM 	79.5 x 68 x 16.5 mm	85 x 75 x 20 mm - Transmitter or receiver dimensions	250 x 54 x 37 mm
Manufacturer / Brand	ATTE	DAHUA	LEGRAND
Guarantee	2 years	3 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00