






	SOUND LEVEL METER UT-353 UNI-T	END CLAMP PV-KK/40-50/B FOR SOLAR PANELS 40 mm	FREEZE FREEZE/300 SPRAY 300 ml AG TERMOPASTY	POWER DISTRIBUTION UNIT LE-049419 (6 OUTLETS) 1.5 m LEGRAND	DUAL SMART LIGHT TOUCH SWITCH ATLO-TB2- TUYA Wi-Fi. Tuya Smart
					
	15.79 EUR 15.79 EUR	0.56 EUR 0.56 EUR	5.19 EUR 5.19 EUR	39.25 EUR 39.25 EUR	10.16 EUR 10.16 EUR
Material	...	Aluminum
Package	Spray 300 ml
Height	...	40 mm
Hole diameter	...	9 mm
Total maximal current	16 A	...
Application	Ideal for fault finding with the thermal method, the so-called "cold solders" and micro cracks in printed circuit boards	...	Works with lighting - switching on/off
mounting screw	...	—
Maximal total load	3680 W	...
Sound level measuring range	30 dB ... 130 dB ± 1.5 dB @ 0.1 dB
Rated voltage	230 V AC / 50 Hz	100 ... 240 V AC, 50 / 60 Hz
Sampling frequency	• 8 Hz • 1 Hz
Number of outlets	6 grounded outlets 16A/250V - CEE 7/5	...
Automatic delayed fuse	—	...
Maximum power	300 W (for each output)
Frequency band	31.5 Hz ... 8 kHz
Rated current	max. 10 A
Microphone type	Condenser microphone : 1/2 "
Number of buttons	2 (touch)
Nominal voltage of surge suppressor	275 V / 50 Hz	...
Number of outputs	2
Protection level of surge suppressor	< 1.5 kV (L/N)	...
Connector type	screw terminals
Nominal stroke current	1.5 kA (L/N) - (8/20µs)	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Switch	with light indication	...
Length of the cable	1.5 m	...
Power supply	3 x 1.5V, type AAA/LR03 battery - included
Manufacturer / Brand	UNI-T	...	AG TERMOPASTY	LEGRAND	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Hold - stopping the meter reading, • Writing the value MAX / MIN, • Large, readable LCD display with backlight, • Automatically turns off the device after 5 min, • Over-range indicator, • Low battery indicator 	...	Spray formulation with a straw for easy application in hard-to-reach places	<ul style="list-style-type: none"> • Mounting brackets for screwing the device to a flat surface or mounting with fastening ties • The body of the device rotates in the range of 180° relative to the mounting brackets • Outlets protected with a protection shutter • LED indication : Power supply, Overvoltage protection 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication • Backlit, touch control panel • The product does not fit standard mounting boxes with a diameter of 60 mm
Housing	Plastic	Plastic + Acrylic glass (plexiglass)
Color	...	Black	White
Operation temp	0 °C ... 40 °C	-20 °C ... 50 °C
Permissible relative humidity	≤ 80 % (non-condensing)	≤ 80 %
Weight	0.08 kg	0.26 kg	0.25 kg	0.59 kg	0.134 kg
Dimensions	150 x 52 x 27 mm	50 x 43 x 30 mm	Ø 53 x 237 mm	423 x 66 x 100 mm	86 x 86 x 34 mm
Guarantee	2 years	2 years	...	2 years	2 years