






	COAXIAL CABLE TRI-LAN-400.50 Ω	WORK GLOVES WG-422/L Bee-Smart WONDER GRIP	RUBBER MAT MB-GUM/50	MONITORS DESK MOUNT MC-691 MACLEAN	EXTENSION CORD WITH GROUNDING PS-3X1.0-1.5M/W 1.5 m
					
	2.74 CHF 2.74 CHF	5.39 CHF 5.39 CHF	6.15 CHF 6.15 CHF	59.49 CHF 59.49 CHF	4.59 CHF 4.59 CHF
Length of the cable	1.5 m
Mounting standard	VESA 75, VESA 100	...
Wire gauge	3 x 1 mm ²
Screen size range	13 " ... 27 "	...
Rated voltage	230 V AC / 50 Hz
In section	100 m . Price for 1m when buying a whole roll
Bearing capacity	8 kg	...
Total maximal current	10 A
Maximal total load	2300 W
Application	...	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly 	<ul style="list-style-type: none"> • Area covering, • Soundproofing
Number of outlets	1 x CEE 7/5
Inner conductor	Ø 2.7 mm Cu ± 0.02 mm Wire
Tilt adjustment	-45 ° ... 45 °	...
Fuse	—
Horizontal rotation	180 °	...
Switch	—
Dielectric	Ø 7.2 mm Physical foam
Color	...	Black + Blue	Black	Black	White
Rotation in the plane of the screen	360 °	...
Mount tube diameter	Ø 35 mm	...
Shield	Foil - Al/PET
Material	...	Polyester + latex coating (palm coated)	SBR granulate + polyurethane binder
Weight	2.4 kg	6 kg	0.17 kg
Braid	168 x Ø 0.15 mm Stranded wire CuSn
Impedance	50 Ω
Outer coating	Ø 10.3 mm ± 0.20 mm PE
Dimensions	500 x 500 x 10 mm	1330 x 550 x 83 mm	...
Supported norms	...	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C 	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating 	<ul style="list-style-type: none"> • Rough structure • Granule fraction : 0.5 ... 4 mm • Insulation • High fatigue strength of the material • Weatherproof • Very easy and quick assembly
Size	...	9 / L
Manufacturer / Brand	...	WONDER GRIP	...	MACLEAN	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Cable attenuation at 100m section	Temperature : 20 °C				
	2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz
Maximum transmitted power	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz
Guarantee	2 years	2 years	2 years

