







	<a href="#">WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps</a>	<a href="#">3 PCS SET ACCESS POINT +ROUTER MAX18-3 Wi-Fi 6, 2.4 GHz, 5 GHz DAHUA</a>	<a href="#">HUB USB 2.0 Y-2140 80 cm</a>	<a href="#">TRIPLE SMART LIGHT SWITCH ATLO-WB3/K-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">ACCESS CONTROLLER ASI3213G-MW DAHUA</a>
						
	2441.17 CZK 2441.17 CZK	2769.23 CZK 2769.23 CZK	4867.69 CZK 4867.69 CZK	118.83 CZK 118.83 CZK	267.26 CZK 267.26 CZK	12695.38 CZK 12695.38 CZK
Sensor	SmartSens CMOS - 2 Mpx	...	...	...	...	CMOS
Application	...	...	...	...	Works with lighting - switching on/off	...
Matrix size	...	...	...	...	...	2 Mpx
In package	...	...	<b>3 pcs</b>	...	...	...
Connectors	...	...	...	• 1 x plug - USB-A • 4 x socket - USB-A	...	...
Length of the cable	...	...	...	80 cm	...	...
Rated voltage	...	...	...	...	100 ... 240 V AC, 50 / 60 Hz	...
USB standard	...	...	...	2.0	...	...
Lens	2.0 mm F1.2	...	...	...	...	...
Resolution	1920 x 1080 px - 1080p	...	...	...	...	1920 x 1080 - 1080p
View angle	140 °	...	...	...	...	...
Maximum power	...	...	...	...	600 W (for each output)	...
Rated current	...	...	...	...	max. 10 A	...
Number of buttons	...	...	...	...	3	...
Number of outputs	...	...	...	...	3	...
Connector type	...	...	...	...	screw terminals	...
proximity reader built-in	Unique EM 125kHz	...	...	...	...	...
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...	...	...	...	...
Frequency range	...	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz	2.4 GHz, 5 GHz	...	...	...
Wireless	...	...	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n	...	...	...	...	...
Standard	...	...	...	...	...	TCP/IP
IR illuminator	5 ... 10 m	...	...	...	...	✓
LED illuminator	—	...	...	...	...	✓
Temperature measurement	...	...	...	...	...	—
Temperature measurement range	...	...	...	...	...	—
Antenna type	...	• 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated	• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in	...	...	...
Mobile phones support	The <a href="#">Tuya Smart</a> free application on Android The <a href="#">Tuya Smart</a> free application on iOS	...	...	...	• The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS	...
Accuracy of temperature measurement	...	...	...	...	...	—
Standards	...	IEEE 802.11 b/g/n/ac	• LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax	...	...	...
Image compression method	H.265 / H.264	...	...	...	...	...
Supported audio formats	G.711	...	...	...	...	...
Face recognition distance	...	...	...	...	...	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in	...	...	...	...	...	• 13.56 MHz S50 • Memory of 1500 RFID cards
Internal memory	...	...	...	...	...	Support storage of 150 000 records

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Video output	...	...	...	...	...	...	—
Baud rates	...	• Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps	574 Mbps + 1201 Mbps	...	...	...	...
RS-485 interface	...	...	...	...	...	...	✓
RS-232 interface	...	...	...	...	...	...	—
Wiegand interface	...	...	...	...	...	...	—
USB	...	...	...	...	...	...	1 x USB 2.0
Memory card slot	...	...	...	...	...	...	—
Alarm inputs / outputs	...	...	...	...	...	...	1 / 1 - Relay outputs
LAN ports	...	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN	3 x 10/100/1000 Mbps	...	...	...	...
Audio	...	...	...	...	...	...	Voice message
Network interface	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi	...	...	...	...	...	1 x 10/100 Base-T (RJ-45)
LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN	...	...	...	...	...
SIM socket	...	1 x mini SIM	...	...	...	...	...
Network protocols	...	...	...	...	...	...	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	...	...	...	...	...	...	Built-in
Permissible relative humidity	...	...	5 % ... 95 %	...	...	≤ 80 %	...
DDNS	...	✓	...	...	...	...	...
DHCP server	...	✓	...	...	...	...	...
ONVIF	...	...	...	...	...	...	—
Firmware update	...	✓	...	...	...	...	...
Default IP address	...	...	...	...	...	...	192.168.1.108
Default admin user / password	...	...	...	...	...	...	admin / - The administrator password should be set at the first start
Protections	...	WEP, WPA/WPA2, WPA- PSK/WPA2-PSK	WPA2	...	...	...	...
Web browser access ports	...	...	...	...	...	...	80, 37777
Management interface	...	Web browser	...	...	...	...	...
PC client access ports	...	...	...	...	...	...	37777
Transmitter power	...	< 20 dBm	...	...	...	...	...
Main features	...	• Built-in 5-port switch • RESET button • Remote management	• Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions	...	...	• Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication	...
Mount	Surface-mounted	...	...	...	...	...	...
Operation temp	-20 °C ... 55 °C	...	-10 °C ... 55 °C	...	...	-20 °C ... 50 °C	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• ATLO-DBC5/CHIME wireless support</li> <li>• Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay</li> <li>• Micro SD memory cards up to 256GB support (possible local recording)</li> <li>• Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording,</li> <li>• Motion Detection,</li> <li>• PIR detector,</li> <li>• Indoor proximity cards and key-fobs reader,</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode,</li> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bidirectional communication,</li> <li>• Noise and echo reduction</li> <li>• Full support via network</li> <li>• 5 on-line users,</li> <li>• Possibility to work in cloud - you don't need to redirect the ports,</li> <li>• Video PUSH personal messaging - Motion Detection,</li> <li>• Video recording - Motion Detection, Doorbell button,</li> <li>• Automatic events notification via Email messages</li> <li>• Lock control - Relay output</li> <li>• Tamper protections</li> <li>• Google Home, Amazon Echo compliance</li> </ul>	...	...	...	...	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera - 4.3" capacitive touch screen, 480 x 272 px</li> <li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li> <li>• 1500 users</li> <li>• Software update via network</li> <li>• Real-time Surveillance</li> <li>• Multiple Authentication</li> <li>• Take face image after swiping card</li> <li>• Auto-Registration</li> <li>• Backup to USB drive (pendrive, external drive)</li> <li>• Output button support</li> <li>• Door status detection</li> <li>• Lock control</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Auto-uploads alarm messages to Master or client station after entering the duress code to open the door</li> <li>• Ability to work with reed switch and signalling the door being opened too long</li> <li>• 128 General Purpose Schedules</li> <li>• Unlocking the transition only when more than one user is present</li> <li>• Tamper protections</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 12 V DC / 1 A (power adapter included)</li> <li>• 48 V PoE (802.3af)</li> </ul>	12 V DC / 1 A (power adapter included)	12 V DC / 1.5 A (power adapter included)	...	...	12 V DC / 1.5 A (power adapter included)
Power consumption	...	...	≤ 12 W	...	...	≤ 18 W
Housing	Aluminum + Plastic (ABS)	...	...	...	Plastic	Plastic (ABS)
Color	Silver	...	...	...	White	Black + Silver
"Index of Protection"	IP44	...	...	...	...	—
Operation temp	...	...	...	...	...	-10 °C ... 55 °C
Weight	<ul style="list-style-type: none"> <li>• 0.22 kg - Wireless Video Doorbell</li> <li>• 0.046 kg - rain cover</li> </ul>	0.42 kg	0.23 kg	0.03 kg	0.102 kg	<ul style="list-style-type: none"> <li>• 0.22 kg (without stand)</li> <li>• 0.24 kg (with stand)</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 141 x 87 x 25 mm - Wireless Video Doorbell</li> <li>• 147 x 94 x 40 mm - rain cover</li> </ul>	238 x 149 x 33 mm	95 x 95 x 73 mm	65 x 23 x 19 mm	87 x 86 x 41 mm	<ul style="list-style-type: none"> <li>• 116 x 107 x 22 mm (without stand)</li> <li>• 116 x 107 x 78 mm (with stand)</li> </ul>
Supported languages	...	...	...	...	...	English
Manufacturer / Brand	...	...	DAHUA	UNITEK	...	DAHUA
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00