



	ACCESS POINT +ROUTER RG-M18 Wi-Fi 6, 2.4 GHz, 5 GHz, 547 Mbps + 1201 Mbps REYEE	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500T-Z- A-2712-S2 - 5 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA
		
	175.67 CAD 175.67 CAD	204.65 CAD 204.65 CAD
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Frequency range	• 2.4 GHz, • 5 GHz ,	...
Antenna type	2x2 MU-MIMO - built-in • 4 dBi @ 2.4 GHz - 2 pcs • 6.8 dBi @ 5 GHz - 2 pcs	...
Standards	IEEE 802.11ax Wi-Fi 6	...
Baud rates	547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz	...
Resolution	...	2880 x 1620 - 5 Mpx, HD- CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p, HD- CVI only , 960 x 576 - 960H, PAL
LAN ports	2 x 10 / 100 / 1000 Mbps - RJ45	...
Lens	...	2.7 ... 12 mm - Motozoom - The camera does not have auto-focus function
WAN interface	1 x 10 / 100 / 1000 Mbps - RJ45	...
Port USB	—	...
LED indicators	Power / System / Mesh, Signal indicator	...
View angle	...	• 107 ° ... 34 ° (manufacturer data) • 102 ° ... 34 ° (our tests result)
DDNS	—	...
Range of IR illumination	...	60 m
DHCP server	✓	...

IR illuminator support	...	ICR - Movable InfraRed filter
Firmware update	✓	...
IR illuminator power adjustment	...	Automatic
Protections	<ul style="list-style-type: none"> • WPA/WPA2 • Black list • parental control • SSID hiding • Firewall 	...
Video output	...	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω
S/N ratio	...	> 65 dB
Operation modes	<ul style="list-style-type: none"> • Repeater • Router • Access Point • WISP 	...
Audio	...	Microphone built-in - HD-CVI only
Management interface	<ul style="list-style-type: none"> • Configuration using the Ruijie Reyeeye application • Remote management • Web browser 	...
Mobile phones support	Android: Free application Ruijie Reyeeye iOS (iPhone): Free application Ruijie Reyeeye	...
Default IP address	192.168.110.1	...
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	...



Main features	...	<ul style="list-style-type: none"> • Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines • Privacy zones - max. 8
OSD menu	...	OSD menu available via DAHUA recorder
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C



Main features	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • OFDMA • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Load balance • WLAN : max. 6 x BSSID • IPv4/IPv6 - Static routing • PPPoE • IPTV • WMM support (QoS mechanism of the 802.11e standard) • VPN support : PPTP VPN Server / Client • Guest Network - a separate and secure network for guests • Support for Reye Mesh technology • System logs • RESET button • MESH button 	...
Housing	Plastic	Dome, Aluminum
Power supply PoE	—	...
Power supply	12 V DC / 1.5 A (included)	12 V DC / 550 mA
Power consumption	max. 18 W	≤ 6.6 W
Operation temp	-10 °C ... 45 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
Weight	0.36 kg	0.57 kg
Dimensions	91 x 91 x 181 mm	Ø 122 x 104 mm
Manufacturer / Brand	RUIJIE / REYEE	DAHUA
Guarantee	3 years	3 years