



	EXTENDER HDMI+USB-EX-100-4K	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE17D0T-IT3F(2.8mm) - 1080p Hikvision
		
	204.02 EUR 204.02 EUR	65.08 EUR 65.08 EUR
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
Sensor	...	Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD	...
Resolution	...	1920 x 1080 - 1080p 960 x 576 - 960H, PAL
Lens	...	2.8 mm
Maximal transmission range	<ul style="list-style-type: none"> • 70 m UTP cat. 6 @ 4K UHD, • 70 m UTP cat. 5, 5e @ 1080p • 50 m UTP cat. 5e @ 4K UHD (our tests result) 	...
View angle	...	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 101 ° (our tests result)
Range of IR illumination	...	40 m
IR illuminator power adjustment	...	Automatic
Main features	<ul style="list-style-type: none"> • Very good image quality with no visible distortions caused by compression • No delays in video transmission • No delays in mouse control operations • Transition of the HDMI signal in the transmitter • S/PDIF output 	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / CVBS, BNC socket
OSD menu	...	OSD menu available via recorder
Operation temp	-20 °C ... 60 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...

Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • Transmitter 5 V DC / 2 A (power adapter included) • Receiver 5 V / 2 A (power adapter included) 	12 V DC / 330 mA
Power consumption	...	≤ 3.9 W
Housing	...	Compact - Metal + Plastic
Color	...	White + Black
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	0.29 kg	0.33 kg
Dimensions	150 x 107 x 28 mm - Transmitter or receiver dimensions	217 x 79 x 75 mm
Supported languages	...	English
Manufacturer / Brand	...	Hikvision
SAP Code	...	300512834
Guarantee	2 years	3 years