



	<u>ELECTRICAL INSTALLATION BOX INTO THERMAL INSULATION KUZ-VO-KB KOPOS</u>	<u>ACCESS CONTROLLER ASI1212F DAHUA</u>
		
	28.62 EUR 28.62 EUR	229.00 EUR 229.00 EUR
Cards support	...	13.56 MHz S50
Reading distance of prox-keys	...	1 ... 3 cm
Keyboard built-in	...	—
Number of sections	1, 2	...
Autonomous operation	...	✓
Battery backup support	...	—
Input lines	...	3
Voltage insulation	~ 400 V	...
Output lines	...	3
Identification time	...	< 1.5 s
Communication	...	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
RS-485 interface	...	✓
RS-232 interface	...	—
Wiegand interface	...	✓
Network interface	...	10/100 Base-T
Default IP address	...	192.168.1.108
Material	Non-halogen plastic	...
Color	Light gray	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
USB	...	—
Memory card slot	...	—
Thickness of the insulating layer	80 ... 140 mm	...
Internal memory	...	Support storage of 150 000 records
Mounting holes distance	60 mm, 71 mm	...
Power supply	...	12 V DC / 1 A

Main features	<ul style="list-style-type: none"> • for insulating systems • temperature range : -25 °C ... 60 °C • flammability index : 850 °C • adjustable depth of the box • Guides for attaching the TS35 rail • Mounting screws, opening lid, rubber gasket - included 	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC
"Index of Protection"	IP30 / IP44	—
Operation temp	...	-10 °C ... 45 °C
Permissible relative humidity	...	5 ... 90 % (non-condensing)
Dimensions	196 x 156 x 86 ... 146 mm (box) 210 x 170 x 12 mm (cover)	115 x 115 x 32 mm
Weight	0.558 kg	0.22 kg
Supported languages	...	English
Manufacturer / Brand	KOPOS	DAHUA
Guarantee	2 years	3 years