





	INSULATION STRIPPER HT-700D	ACCESS POINT 4G LTE +ROUTER RUT200 2.4 GHz 300 Mbps Teltonika	MULTI-SOCKET PLUG WITH SWITCH MCE-142 3680 W MACLEAN ENERGY	MULTI-SOCKET PLUG LE-50639 3680 W LEGRAND
				
	9.81 CAD 9.81 CAD	153.46 CAD 153.46 CAD	4.96 CAD 4.96 CAD	9.52 CAD 9.52 CAD
Frequency range	...	2.4 GHz
Material	Metal / PET
Rated voltage	230 V / 50 Hz	230 V / 50 Hz
Maximal total load	3680 W	3680 W
Total maximal current	16 A	16 A
Antenna type	...	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Application	Wire : 0.2 ... 6 mm ²
Socket type	CEE 7/5
Plug type	CEE 7/7
Number of outlets	• 1 pcs 2P+Z, • 2 pcs 2P - flat	3 pcs 2P+Z
Grounding	✓	✓
Standards	...	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G
Housing	Plastic	Plastic
Color	White	White / Gray
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.234 Mbps (4G / 3G / 2G)
LAN ports	...	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
Transmitter power	...	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM
LED indicators	...	Power, WAN, WLAN, LAN, LTE (4G / 3G / 2G), Signal indicator
Network type	...	4G, 3G, 2G
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓

Protections	...	<ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA-PSK/WPA2-PSK • WPA-EAP • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering
Management interface	...	Web browser, Teltonika RMS application, SMS
Main features	<ul style="list-style-type: none"> • Self-adjusting mechanism according to wire size provides excellent wire stripping without damaging the conductor • Possibility to use for flat telephone cables of 8 mm width • Adjustable stop with lengths scale • Cutter • High durability tool, made from high quality materials 	<ul style="list-style-type: none"> • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	Switch built-in - with light indication	...
Power supply	...	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1
Power consumption	...	≤ 6.5 W
Operation temp	...	-40 °C ... 75 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.21 kg	0.13 kg	0.1 kg	0.1 kg
Dimensions	170 x 88 x 21 mm	83 x 80 x 25 mm	95 x 72 x 55 mm	138 x 52 x 74 mm
Manufacturer / Brand	...	Teltonika	MACLEAN ENERGY	LEGRAND
Guarantee	2 years	2 years	2 years	2 years