






	RFID PROXIMITY CARD ATLO-114N*P25	CABLE OUTLET DPK1.01/49-SIMON54	EXTENDER HDMI+USB- EX-100-4K-V2	BOX FOR FLUSH- MOUNTED CONNECTIONS FOR HOUSEHOLD APPLIANCES PK- AGD/2/EPN Elektro-Plast	TERMINAL COVER TBC-09
					
	13.10 EUR 13.10 EUR	6.95 EUR 6.95 EUR	249.76 EUR 249.76 EUR	15.48 EUR 15.48 EUR	0.57 EUR 0.57 EUR
Application	Power supply adapters of the RSP-200/320 and LRS-200/350 series
Support	...	Simon 54 product series, for Nature, Premium frames
Number of modules	...	1
Material	Plastic, (transparent)
In package	25 pcs The price for package
Number of terminals	5 pcs : 3 x 6 mm ² - Quick-connector	...
Standard	Unique EM 125kHz
Compatibility	EM4100/4102
Possibility of programming the serial number (ID)	—
Supported HDMI resolutions	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD
Ability to write to internal memory	—
Serial Number overprint	✓
Housing	...	Non-halogen plastic, PC
Maximal transmission range	100 m UTP cat. 5e, 6 @ 4K UHD ,
Material	Plastic	...
Color	...	Matt black	...	White	...
Max. number of receivers working in the same time	253
"Index of Protection"	...	IP20	...	IP40	...
Protocols	HDbiT
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Audio transmission via network
Main features	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A, • Range : ~ 15 cm, • The TK-4100 chip 	<ul style="list-style-type: none"> • Cable diameter : 6.2 ... 14.5 mm • Claw or screw mounting • Installation in flush-mounted enclosures • Aesthetic and solid construction 	<ul style="list-style-type: none"> • The devices do not require direct connection, they also operate via the LAN network • The need for a separate power supply for the transmitter and receiver 	<ul style="list-style-type: none"> • Claw or screw mounting • Cover fastened with latches • Flat housing profile : 22 mm 	...
Manufacturer / Brand	ATLO	KONTAKT Simon	...	Elektro-Plast Nasielsk	...
Power supply	<ul style="list-style-type: none"> • Transmitter 5 V DC / 1 A (power adapter included) • Receiver 5 V / 1 A (power adapter included)
Operation temp	-20 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Weight	0.008 kg	0.05 kg	0.31 kg	0.11 kg	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	86 x 54 x 2 mm	<ul style="list-style-type: none"> • 75 x 75 x 55 mm • 22 mm - mounting depth 	133 x 90 x 26 mm - Transmitter or receiver dimensions	113 x 117 x 45 mm	89 x 10 x 4 mm
Guarantee	2 years	6 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00