

	<a href="#">EXTENDER USB-EX-150/4-USB</a>	<a href="#">CONNECTOR STRIP KE-CPO-30A-3P SIMET</a>	<a href="#">ANGULAR COMPRESSION PLUG F-WK/ZAC-TRI113</a>
			
	62.20 EUR 62.20 EUR	2.28 EUR 2.28 EUR	0.87 EUR 0.87 EUR
Number of terminal pairs	...	3	...
Connector type	...	terminals	...
Nominal voltage	...	450 V	...
Rated current	...	76 A	...
Wire gauge	...	16 mm <sup>2</sup>	...
Dielectric	...	Porcelain	...
Connector type	...	...	"F" Angular plug
Color	...	White	...
Attachment of connector elements	...	...	Compression mounting
Connectors	<ul style="list-style-type: none"> <li>• Transmitter :</li> <li>- 1 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> <li>• Receiver :</li> <li>- 4 x USB-A</li> <li>- 1 x RJ-45 shielded socket</li> </ul>	...	...
Application	...	...	Coaxial cable
Manufacturer / Brand	...	SIMET	...
Dielectric diameter	...	...	max. 6.5 mm
Impedance	...	...	75 Ω
Range	<ul style="list-style-type: none"> <li>• 150 m - USB 2.0 @ UTP cat. 6,</li> <li>• 100 m - USB 2.0 @ UTP cat. 5e</li> </ul>	...	...
UTP category	5e / 6 / 6A / 7	...	...
Wire mounting	...	...	Pressing
Cable diameter	...	...	max. 8.5 mm
Shield fastening	...	...	Compression mounting
Material	...	...	Brass (Nickel-platted)
Power supply	5 V DC / 1 A (power adapter included) - Receiver	...	...
Watertightness	...	...	✓
Example of application	...	...	Triset113
Operation temp	-20 °C ... 60 °C	...	...

Housing	Metal	...	...
Main features	<ul style="list-style-type: none"> <li>• USB 2.0 - High-Speed (480 Mb/s) (compatible with older)</li> <li>• Supports 4 USB 2.0 inputs and 1 USB 2.0 output</li> <li>• The transmitter is powered from the source device - no additional power supply is required</li> <li>• The device supports a cascade of gigabit switches, which allows to increase the transmission distance</li> <li>• Lightning protection, surge protection, ESD protection</li> <li>• Easy installation - Plug&amp;Play USB device type</li> </ul>	...	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Very low loss in the whole operating band</li> <li>• Perfect matching to the transmission line within the whole operating band</li> <li>• Watertightness of connector with cable connection</li> <li>• Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric</li> <li>• Properly compressed connection is highly resistant to break</li> <li>• Many patent-pending solutions</li> <li>• To crimp use the crimping tool ZAC/MSR-2K, HT-5082R</li> </ul>
Weight	0.12 kg	...	0.024 kg
Dimensions	77 x 61 x 21 mm	22 x 27 x 48 mm	12 x 39 x 27 mm
Guarantee	2 years	2 years	2 years