




	<a href="#">MODEM 4G LTE, MOBILE ROUTER TL-M7000 Wi-Fi 300Mb/s TP-LINK</a>	<a href="#">MOUNTING PROFILE USP-SM-1100 FOR SOLAR PANELS</a>	<a href="#">REAR MOUNTING BASE USP-UDMK-T FOR SOLAR PANELS</a>
			
	70.84 EUR 70.84 EUR	13.87 EUR 13.87 EUR	7.37 EUR 7.37 EUR
Frequency range	2.4 GHz	...	...
Material	...	Aluminum	Aluminum
Antenna type	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna	...	...
Standards	IEEE 802.11 b/g/n, 4G LTE, 3G HSPA+/HSPA/UMTS	...	...
Baud rates	<ul style="list-style-type: none"> <li>• LTE : 150 / 50 Mbps,</li> <li>• 11n : 300 Mbps,</li> <li>• 11g : 54 Mbps,</li> <li>• 11b : 11 Mbps</li> </ul>	...	...
Network type	<ul style="list-style-type: none"> <li>• 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz</li> <li>• 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz</li> <li>• 3G : HSPA+/HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz</li> </ul>	...	...
LAN ports	—	...	...
Ports	<ul style="list-style-type: none"> <li>• 1 x micro USB - Battery charging</li> <li>• 1 x SIM socket</li> </ul>	...	...
Receiver sensitivity	<ul style="list-style-type: none"> <li>• 11b 11 Mbps : -87.5 dBm</li> <li>• 11g 54 Mbps : -74 dBm</li> <li>• 11n HT20 MCS7 : -70 dBm</li> <li>• 11n HT40 MCS7 : -68 dBm</li> </ul>	...	...
Transmitter power	< 20 dBm	...	...

Main features	<ul style="list-style-type: none"> <li>• ON/OFF button</li> <li>• RESET button</li> <li>• LED diodes : WiFi, INTERNET, Battery</li> <li>• Transmission encryption : WPA-PSK/WPA2-PSK</li> <li>• MAC addresses filtering</li> <li>• SSID hiding</li> <li>• DHCP server</li> <li>• DHCP client list</li> <li>• Max. number of supported devices : 10</li> <li>• Backup time max. 8 h</li> <li>• Remote management - tpMiFi application</li> <li>• System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad), Windows Phone</li> </ul>	...	...
Power supply	<ul style="list-style-type: none"> <li>• 2000 mAh Battery</li> <li>• 5 V DC / 1 A Charging via USB port</li> </ul>	...	...
Operation temp	0 °C ... 35 °C	...	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...	...
Weight	0.09 kg	0.21 kg	0.16 kg
Dimensions	94 x 57 x 20 mm	1100 x 50 x 50 mm	96 x 80 x 72 mm
Manufacturer / Brand	TP-LINK	...	...
Guarantee	2 years	2 years	2 years