



	<a href="#">EXPANSION PLUG KS-12/8X120 KLIMAS</a>	<a href="#">SMART CONTROLLER FOR ROLLER SHUTTERS SRW-01 Wi-Fi 230 V AC ZAMEL</a>	<a href="#">SMART LED LIGHTING CONTROLLER SLW-01 Wi-Fi, SUPLA 12 ... 24 V DC ZAMEL</a>	<a href="#">EXTENDER EXT-POE2 PULSAR</a>
				
	0.42 GBP 0.42 GBP	47.95 GBP 47.95 GBP	32.95 GBP 32.95 GBP	24.53 GBP 24.53 GBP
Support	...	SUPLA	SUPLA	...
Standards	...	...	...	PoE : IEEE 802.3at, IEEE 802.3af
Material	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>	...	...	...
Input voltage	...	...	...	42 ... 57 V DC
Drilling diameter	12 mm	...	...	...
Output voltage	...	...	...	42 ... 57 V DC
Expansion plug length	80 mm	...	...	...
Rated voltage	...	230 V AC	12 ... 24 V DC	...
Maximal total load	...	...	140 W	...
Relay maximal load	...	5 A	...	...
Connector	...	...	...	3 x RJ-45 socket
Screw dimensions	Ø 8 x 120 mm, SW-13	...	...	...
LED indicators	...	...	...	Link/Act
Total maximal current	...	...	6 A ( 2 A / Channel )	...
Application	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul>	roller shutters, roof windows, awnings, drop-down screens, curtains	Works with LED lighting - (RGB) 12-24V LED strips	...
Supported data rates	...	...	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates : 10 / 100 Mbps - Fast Ethernet</li> </ul>
Maximal outputs load	...	350 W	LED RGB 12 V : 5 m - 70 W LED RGB 24 V : 10 m - 140 W	...
Number of inputs	...	2 pcs	1	1
Number of outputs	...	1 pcs ( Motor )	3	2
Connector type	...	screw terminals	screw terminals	...
Output power	...	...	...	max. 15.4 W / port PoE max. 20 W (total)
Protections	...	...	...	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Mobile phones support	...	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	...
Operation temp. / Relative humidity	...	...	...	-10 ... 40 °C / 10 ... 90 %

Main features	...	<ul style="list-style-type: none"> <li>• Control from a Web browser,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Control of color, color temperature, brightness, effect, allows any interior design</li> </ul>	...
Housing	...	Plastic	Plastic	Metal
"Index of Protection"	...	IP20	IP20	...
Color	...	Green	Green	...
Operation temp	...	-10 °C ... 55 °C	-20 °C ... 50 °C	...
Weight	...	0.030 kg	0.030 kg	0.11 kg
Dimensions	...	47.5 x 47.5 x 20 mm	47 x 47 x 20 mm	81 x 77 x 26 mm
Manufacturer / Brand	KLIMAS	ZAMEL	ZAMEL	PULSAR
Guarantee	2 years	2 years	2 years	2 years