







	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps	3 PCS SET ACCESS POINT +ROUTER MAX18-3 Wi-Fi 6, 2.4 GHz, 5 GHz DAHUA	HUB USB 2.0 Y-2140 80 cm	TRIPLE SMART LIGHT SWITCH ATLO-WB3/K-TUYA Wi-Fi, Tuya Smart	ACCESS CONTROLLER ASI3213G-MW DAHUA
						
	2441.17 CZK 2441.17 CZK	2769.23 CZK 2769.23 CZK	4867.69 CZK 4867.69 CZK	118.83 CZK 118.83 CZK	267.26 CZK 267.26 CZK	12695.38 CZK 12695.38 CZK
Sensor	SmartSens CMOS - 2 Mpx	CMOS
Application	Works with lighting - switching on/off	...
In package	3 pcs
Matrix size	2 Mpx
Connectors	• 1 x plug - USB-A • 4 x socket - USB-A
Length of the cable	80 cm
USB standard	2.0
Lens	2.0 mm F1.2
Rated voltage	100 ... 240 V AC, 50 / 60 Hz	...
View angle	140 °
Resolution	1920 x 1080 px - 1080p	1920 x 1080 - 1080p
Maximum power	600 W (for each output)	...
Rated current	max. 10 A	...
Number of buttons	3	...
Number of outputs	3	...
Connector type	screw terminals	...
proximity reader built-in	Unique EM 125kHz
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Frequency range	...	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz	2.4 GHz, 5 GHz
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Standard	TCP/IP
IR illuminator	5 ... 10 m	✓
LED illuminator	—	✓
Temperature measurement	—
Temperature measurement range	—
Antenna type	...	• 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated	• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS	...
Accuracy of temperature measurement	—
Standards	...	IEEE 802.11 b/g/n/ac	• LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax
Image compression method	H.265 / H.264
Supported audio formats	G.711
Face recognition distance	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in	• 13.56 MHz S50 • Memory of 1500 RFID cards
Internal memory	Support storage of 150 000 records

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Video output	—
Baud rates	...	• Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps	574 Mbps + 1201 Mbps
RS-485 interface	✓
RS-232 interface	—
Wiegand interface	—
USB	1 x USB 2.0
Memory card slot	—
Alarm inputs / outputs	1 / 1 - Relay outputs
LAN ports	...	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN	3 x 10/100/1000 Mbps
Audio	Voice message
Network interface	...	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi	1 x 10/100 Base-T (RJ-45)
LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN
SIM socket	...	1 x mini SIM
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	Built-in
Permissible relative humidity	5 % ... 95 %	≤ 80 %	...
DDNS	...	✓
DHCP server	...	✓
ONVIF	—
Firmware update	...	✓
Default IP address	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start
Protections	...	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	WPA2
Web browser access ports	80, 3777
Management interface	...	Web browser
PC client access ports	3777
Transmitter power	...	< 20 dBm
Main features	...	• Built-in 5-port switch • RESET button • Remote management	• Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions	• Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication	...
Mount	Surface-mounted
Operation temp	-20 °C ... 55 °C	...	-10 °C ... 55 °C	-20 °C ... 50 °C	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance 	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3" capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 1500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Auto-uploads alarm messages to Master or client station after entering the duress code to open the door • Ability to work with reed switch and signalling the door being opened too long • 128 General Purpose Schedules • Unlocking the transition only when more than one user is present • Tamper protections
Power supply	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af) 	12 V DC / 1 A (power adapter included)	12 V DC / 1.5 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 12 W	≤ 18 W
Housing	Aluminum + Plastic (ABS)	Plastic	Plastic (ABS)
Color	Silver	White	Black + Silver
"Index of Protection"	IP44	—
Operation temp	-10 °C ... 55 °C
Weight	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	0.42 kg	0.23 kg	0.03 kg	0.102 kg	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand)
Dimensions	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	238 x 149 x 33 mm	95 x 95 x 73 mm	65 x 23 x 19 mm	87 x 86 x 41 mm	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand)
Supported languages	English
Manufacturer / Brand	DAHUA	UNITEK	...	DAHUA
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00