




	ELECTRIC CABLE DY-2.5-BU/750V	ACCESS POINT 4G LTE +ROUTER RUT200 2.4 GHz 300 Mbps Teltonika	ANTENNA AP-5/2.4
			
	9.25 CZK 9.25 CZK	2624.54 CZK 2624.54 CZK	142.91 CZK 142.91 CZK
Frequency range	...	2.4 GHz	2.4 GHz ... 2.5 GHz
Impedance	50 Ω
In section	100 m . Price for 1m when buying a whole roll
Gain	5 dBi ... 7 dBi
Connector	SMA-RP plug
Inner conductor	2.5 mm ² - Cu wire
Antenna type	...	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	...
Horizontal beam width (H)	360 °
Rated voltage	450 / 750 V
Vertical beam width (V)	32 °
Outer coating	Ø 3.3 mm - PVC
Coating color	Blue
Standards	...	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G	...
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.234 Mbps (4G / 3G / 2G)	...
LAN ports	...	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN	...
Transmitter power	...	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM	...
LED indicators	...	Power, WAN, WLAN, LAN, LTE (4G / 3G / 2G), Signal indicator	...
Network type	...	4G, 3G, 2G	...
LTE	...	✓	...
QSS	...	—	...
WDS	...	—	...
DHCP server	...	✓	...

Protections	...	<ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA-PSK/WPA2-PSK • WPA-EAP • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	...
Management interface	...	Web browser, Teltonika RMS application, SMS	...
Main features	...	<ul style="list-style-type: none"> • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	...
Power supply	...	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 	...
Power consumption	...	≤ 6.5 W	...
Operation temp	...	-40 °C ... 75 °C	...
Permissible relative humidity	...	10 % ... 90 % (non-condensing)	...
Weight	...	0.13 kg	...
Dimensions	...	83 x 80 x 25 mm	...
Manufacturer / Brand	...	Teltonika	...
Guarantee	2 years	2 years	2 years