



|                                  |   |   |
|----------------------------------|---|---|
|                                  | <a href="#">AHD MOBILE CAMERA<br/>ATE-CAM-AHD620HD -<br/>1080p 2.8 mm AUTONE</a>  | <a href="#">CONNECTOR WITH<br/>ELASTIC SEALING<br/>F/6.8*P10</a>  |
|                                  |    |   |
|                                  | 122.56 EUR<br>122.56 EUR  | 1.80 EUR<br>1.80 EUR  |
| Standard                         | AHD   | ...   |
| Sensor                           | 1/3 " Sony CMOS IMX323  | ...   |
| Matrix size                      | 2.1 Mpx   | ...   |
| In package                       | ...   | <b>10 pcs The price for package</b>   |
| Resolution                       | 1920 x 1080 - 1080p   | ...   |
| Connector type                   | ...   | "F" Straight plug   |
| Lens                             | 2.8 mm  | ...   |
| Attachment of connector elements | ...   | Twisted-on  |
| Shield fastening                 | ...   | Twisting-on   |
| Wire mounting                    | ...   | —   |
| Application                      | ...   | Coaxial cable   |
| View angle                       | 89 ° (manufacturer data)<br>85 ° (our tests result)   | ...   |
| Range of IR illumination         | 10 m  | ...   |
| Cable diameter                   | ...   | max. 6.8 ± 0.05 mm  |
| S/N ratio                        | ≥ 58 dB   | ...   |
| Impedance                        | ...   | 75 Ω  |
| Material                         | ...   | Metal   |
| Video output                     | 2 x 1 Vpp / 75 Ω - M12, 4-pin socket, Code A  | ...   |
| Main features                    | ...   | <ul style="list-style-type: none"> <li>• Elastic sealing</li> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> </ul> |
| Audio                            | —   | ...   |
| Main features                    | <ul style="list-style-type: none"> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul> | ...   |
| OSD menu                         | —   | ...   |
| Housing                          | Mini, Metal   | ...   |
| Color                            | Black   | ...   |
| Application                      | The camera is designed for installation outside vehicles  | ...   |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                      |   |                 |
|----------------------|---|-----------------|
| Power supply         | 2 x 12 V DC / 420 mA -<br>Powering the cameras with<br>12V DC voltage directly from<br>recorder | ...             |
| Power consumption    | < 10 W (total)  | ...             |
| Operation temp       | -10 °C ... 50 °C  | ...             |
| Weight               | 0.46 kg   | 0.003 kg        |
| Dimensions           | 101 x 82 x 60 mm  | Ø 11 mm x 20 mm |
| Manufacturer / Brand | AUTONE  | ...             |
| Guarantee            | 2 years   | 2 years         |