




	<a href="#">SWITCHING ADAPTER 18V/1A/F-MRP FOR SIGNAL MRP MULTISWITCHES F PLUG</a>	<a href="#">IP CAMERA IPC2124LE-ADF28KMC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200TMO-A-0280B-S6 - 1080p 2.8 mm DAHUA</a>
			
	75.84 SEK 75.84 SEK	1949.48 SEK 1949.48 SEK	796.27 SEK 796.27 SEK
Adapter type	Switching	...	...
Power voltage	100 ... 240 V AC	...	...
Frequency range	50/60 Hz	...	...
Standard	...	TCP/IP	HD-CVI, HD-TVI, AHD, CVBS
Output voltage	18 V DC	...	...
Sensor	...	1/3 " Progressive Scan CMOS	Progressive Scan CMOS
Maximal load	1 A	...	...
Matrix size	...	4 Mpx	2.1 Mpx
Application	SIGNAL MRP Multiswitches	...	...
Output	F plug	...	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
IR illuminator power adjustment	...	...	Automatic
Lens	...	2.8 mm	2.8 mm
View angle	...	• 113 ° (manufacturer data) • 97 ° (our tests result)	• 102 ° (manufacturer data) • 101 ° (our tests result)
Range of IR illumination	...	30 m	60 m
White light LED illuminator range	...	30 m	...
S/N ratio	...	> 52 dB	...
RS-485 interface	...	—	...
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)	...
Video output	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	• Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only
Main stream frame rate	...	25 fps @ 4 Mpx	...
Network interface	...	10/100 Base-T (RJ-45)	...

OSD menu	...	...	OSD menu available via DAHUA recorder
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	32	...
ONVIF	...	✓	...
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>	...
Default IP address	...	DHCP or 192.168.1.13	...
Default admin user / password	...	admin / 123456	...
Web browser access ports	...	80, 554	...
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...
Mobile client access ports	...	80	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...



Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 750 mA</li> </ul>	12 V DC / 410 mA
Power consumption	...	≤ 9 W	≤ 4.9 W
Housing	...	Compact, Metal + Plastic	Dome, Metal + Plastic
Color	...	White	White
"Index of Protection"	...	IP67	IP67
Vandal-proof	...	—	—
Operation temp	...	-30 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.1 kg	0.41 kg	0.44 kg
Dimensions	...	191 75 x 74 mm	Ø 122 x 99 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	...	UNIVIEW	DAHUA
Guarantee	2 years	3 years	3 years