




	SWITCH POE APTI-POE0802G-120W 8-PORT	USB 3.1 ACTIVE EXTENSION CABLE Y-3005 10 m	SWITCH POE RG-NBS3200-24GT4XS-P 24-PORT REYEE
			
	270.40 PLN 270.40 PLN	194.59 PLN 194.59 PLN	4133.00 PLN 4133.00 PLN
Cable	...	USB 3.1 A Plug / USB 3.1 A Socket	...
Length of the cable	...	10 m	...
USB standard	...	3.1	...
LAN ports	10 x RJ45 (8 x PoE (802.3af/at))	...	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 4 x port SFP+ - Uplink
Management	—	...	✓
LED diodes	LAN, PoE
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 8 x LAN & PoE ports 	...	10/100/1000 Mbps - 24 x Gigabit Ethernet 10 Gb/s - 4 x port SFP+
Maximal output power	30 W / port PoE
Switching capacity	128 Gb/s
Maximal total power	120 W	...	370 W
Forwarding rate	95.24 Mpps
MAC addresses table	2k	...	16k
Number of fan coolers	1
Certificates	CE	...	CE, RoHS
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Jumbo Frame	9 kB
Default IP address	10.44.77.200
Operation temp	0 °C ... 55 °C

Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	<ul style="list-style-type: none"> • The used amplifier enables the transmission of the USB signal over a long distance without losing quality and transmission speed • Solid workmanship • Very flexible • Supported data rates : 5 Gb/s • Power transmitted : 900 mA 	<ul style="list-style-type: none"> • Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reye application) • Access Control List - ACL package filtering based on source and destination IP addresses • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • Up to 16 aggregation groups and up to 8 ports per group • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Operation temp	0 °C ... 50 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Protections	Protection against lightning discharges : 6 kV
Power supply	230 V AC	...	100 V ... 240 AC
Power consumption	≤ 432 W
Weight	0.74 kg	0.51 kg	4.87 kg
Dimensions	220 x 143 x 41 mm	...	440 x 360 x 43 mm
Manufacturer / Brand	APTI	UNITEK	RUIJIE / REYEE
Guarantee	2 years	2 years	5 years