



	SWITCH POE CS4220-16GT-240 16-PORT SFP DAHUA	SWITCH POE CS4228-24GT-240 24-PORT SFP DAHUA
		
	646.71 EUR 646.71 EUR	737.25 EUR 737.25 EUR
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-T (2 x Hi-PoE (802.3bt) + 14 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink, • 2 x SFP 1000 Base-X - Uplink 	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (2 x Hi-PoE (802.3bt) + 22 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink, • 2 x SFP 1000 Base-X - Uplink
Management	✓	✓
Default IP address	192.168.1.110	192.168.1.110
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
LED diodes	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 RJ45 (Uplink) ports, • 1000 Mbps : 2 SFP (Uplink) ports 	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 24 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 RJ45 (Uplink) ports, • 1000 Mbps : 2 SFP (Uplink) ports
Maximal output power	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 16 ports 	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports • 30 W / port PoE 802.3af/at - 3 ... 24 ports
Maximal total power	240 W	240 W
MAC addresses table	8k	8k
Operation modes	<ul style="list-style-type: none"> • Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6 	<ul style="list-style-type: none"> • Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Can be mounted in a Rack 19" cabinet 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Can be mounted in a Rack 19" cabinet
Certificates	CE	CE
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	Metal	Metal
Power supply	100 ... 240 V AC @ 47 ... 63 Hz	100 ... 240 V AC @ 47 ... 63 Hz
Power consumption	max. 265 W	max. 265 W
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	2.41 kg	2.52 kg
Dimensions	440 x 220 x 44 mm, RACK 19", 1U	440 x 220 x 44 mm, RACK 19", 1U
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	5 years	5 years