



	RELAY MODULE 2R-D7 Modbus RTU	ETHERNET + EPOE CONVERTER EOC-73
		
	9.56 EUR 9.56 EUR	12.24 EUR 12.24 EUR
PTZ control	RS-485 / UART TTL	...
Protocol	Modbus RTU	...
In package	...	2 pcs The price for package
LAN ports	...	1 pcs RJ45
Transmission ports	...	1 pcs BNC
Number of inputs	2 pcs	...
Transmission speed	4800 / 9600 / 19200 b/s (default: 9600 b/s)	10 / 100 Mbps Half Duplex
Number of relay outputs	2 pcs	...
Transmission range	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver
Relay maximal load	10 A / 250 V AC , 10 A / 30 V DC	...
Output	2 x NO/NC	...
Protections	...	Short-circuit Protection against electrostatic discharge

Main features	<ul style="list-style-type: none"> • LED indication • The control inputs protected with optocouplers, which allows the use of control signals with voltages in the range of 3.3 V DC ... 30 V DC • The UART interface input is adapted to the installation of gold-pins for signals with voltages adapted to the TTL level (3.3 V DC / 5 V DC) • Possibility to configure the device address (with saving the settings after a power failure) in the range of 1 - 255 (default address 255) • Possibility to set the delay of the relay operation (base unit: 0.1 s, value range: 0.1 s ... 6553.5 s) • Protection against reverse polarity of the input voltage 	<ul style="list-style-type: none"> • Plug & Play • The device works only with recorders and cameras supporting the ePOE standard • Easy installation - doesn't require any configuration of IP nor MAC address • Length of the cable : 10.5 cm
Power supply	7 V ... 24 V DC (power adapter not included)	ePoE
Weight	0.046 kg	0.022 kg (single element)
Dimensions	85 x 49 x 19 mm	65 x 20 x 18 mm (single element)
Guarantee	2 years	2 years