



	SWITCH POE RG-ES226GC-P 24-PORT REYEE	CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P-Z/RGB 10 mm ORNO	WIRELESS DOOR CHIME ATLO-DB-TUYA
			
	2022.00 PLN 2022.00 PLN	5.39 PLN 5.39 PLN	24.27 PLN 24.27 PLN
Signaling mode	Optical - sound signaling
Number of ring-tones	52
Application	...	Works with LED lighting RGB	...
Number of power outputs	...	2 pcs	...
Strip width	...	10 mm	...
Length of the cable	...	140 mm	...
Volume adjustment	4 volume levels, 10 ... 90 dB
"Index of Protection"	...	—	...
Operation range	80 m - in open area
Maximal power voltage	...	48 V	...
LAN ports	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X - Uplink
Management	✓
Frequency band	433.92 MHz ± 0.2
Number of fan coolers	1 pcs
LED diodes	STATUS indicator, PoE, Link/Act
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 24 LAN & PoE ports • 1000 Mbps : 2 SFP ports
Color	...	White	White
Maximal total power	370 W
Switching capacity	52 Gb/s
Forwarding rate	38.69 Mpps
MAC addresses table	8k
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Default IP address	10.44.77.200

Operation modes	<ul style="list-style-type: none"> • Flow Control ON - Data flow control is enabled and all ports can communicate with each other, • Flow Control OFF - Data flow control is disabled and all ports can communicate with each other, • Port Isolation
Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (Ruijie Rejee application) • Can be mounted in a Rack cabinet, • Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • DHCP client • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h 	...	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation
Certificates	CE, RoHS
Protections	Protection against lightning discharges : 4 kV
Housing	Desktop, Metal	Plastic	Plastic
Power supply	100 ... 240 V AC	...	100 ... 240 V AC
Power consumption	≤ 443 W	...	≤ 0.5 W
Operation temp	0 °C ... 40 °C
Weight	4.02 kg	0.002 kg	0.06 kg
Dimensions	440 x 295 x 45 mm	140 x 15 x 5 mm	82 x 82 x 65 mm
Manufacturer / Brand	RUIJIE / REYEE	ORNO	...
Guarantee	3 years	2 years	2 years