



| | | |
|---------------------------------|---|---|
| | IP DECODER NVD0905DH-4I-4K - 12 Mpx, 4K | AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200TMQ- A-0280B-S6 - 1080p 2.8 mm DAHUA |
| |  |  |
| | 48348.73 NOK 48348.73 NOK | 811.64 NOK 811.64 NOK |
| Standard | ... | HD-CVI, HD-TVI, AHD, CVBS |
| Sensor | ... | Progressive Scan CMOS |
| Matrix size | ... | 2.1 Mpx |
| Resolution | ... | 1920 x 1080 - 1080p , 960 x 576 - 960H, PAL |
| Range of IR illumination | ... | 60 m |
| IR illuminator power adjustment | ... | Automatic |
| Lens | ... | 2.8 mm |
| View angle | ... | <ul style="list-style-type: none"> • 102 ° (manufacturer data) • 101 ° (our tests result) |
| Supported resolutions | 9 Channels @ 4000 x 3000 px - 12 Mpx , 9 Channels @ 3840 x 2160 px - 4K , 36 Channels @ 1920 x 1080 - 1080p , 81 Channels @ 1280 x 720 - 720p , 144 Channels @ 704 x 576 - D1 | ... |
| Number of supported screens | 9 pcs | ... |
| Video inputs | <ul style="list-style-type: none"> • 2 x HDMI 4K • 2 x DVI | ... |
| Video outputs | 9 x HDMI | ... |
| Video output | ... | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω |
| Audio outputs | HDMI | ... |
| Network interface | 2 x RJ45 10/100/1000 Base-T | ... |
| Default IP address | 192.168.1.108 | ... |
| Audio | ... | <ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only |
| Default admin user / password | admin / - | ... |

| | | |
|------------------------|---|---|
| Serial ports | <ul style="list-style-type: none"> • 2 pcs RS-232 @ RJ45 • 1 pcs RS-232 @ D-Sub • 1 pcs RS-485 | ... |
| Alarm inputs / outputs | 4 / 4 | ... |
| Main features | ... | <ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • AGC - Automatic Gain Control • Auto White Balance • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines |
| Operation temp | -10 °C ... 55 °C | ... |
| OSD menu | ... | OSD menu available via DAHUA recorder |
| Power supply | 230 V AC | 12 V DC / 410 mA |
| Power consumption | ≤ 70 W | ≤ 4.9 W |
| Housing | ... | Dome, Metal + Plastic |
| "Index of Protection" | ... | IP67 |
| Color | ... | White |
| Vandal-proof | ... | — |
| Operation temp | ... | -40 °C ... 60 °C |
| Weight | 4.70 kg | 0.44 kg |
| Dimensions | 440 x 415 x 76 mm - 1.5 U | Ø 122 x 99 mm |
| Manufacturer / Brand | DAHUA | DAHUA |
| Guarantee | 3 years | 3 years |