




	<a href="#">EXPANSION PLUG KW-10/6X60 KLIMAS</a>	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-8 ROGER</a>	<a href="#">NVR NVR4232-EI 32 CHANNELS WizSense DAHUA</a>
			
	1.92 SEK 1.92 SEK	11883.89 SEK 11883.89 SEK	5711.10 SEK 5711.10 SEK
Standard	...	...	TCP/IP
Number of served transitions	...	8	...
Inputs	...	8	...
Supported resolutions	...	...	max. 16 Mpx - 4608 x 3472 px
Outputs	...	8	...
Material	<ul style="list-style-type: none"> <li>Expansion plug, Polypropylene</li> <li>Screw, Steel galvanized</li> </ul>	...	...
Drilling diameter	10 mm	...	...
Video outputs	...	...	1 pcs HDMI 4K 1 pcs VGA
Number of users	...	max. 8192 - Number of identifiers	...
Expansion plug length	60 mm	...	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Number of permissions per ID	...	32	...
Audio support	...	...	<ul style="list-style-type: none"> <li>32 Channels - Audio from cameras</li> <li>Bi-directional audio streaming support</li> </ul>
Buffer memory	...	8 000 000 events buffer	...
Screw dimensions	Ø 6 x 60 mm, PZ-3	...	...
Audio inputs	...	...	1 pcs CINCH
MCT readers support	...	16 pcs	...
Audio outputs	...	...	1 pcs CINCH
Application	<ul style="list-style-type: none"> <li>Concrete</li> <li>Solid clay brick</li> <li>Solid sand-lime brick</li> </ul>	...	...
Readers connections	...	4 pcs - Wiegand / PRT	...
Number of login points	...	16	...
Number of access terminals	...	32	...
Image compression method	...	...	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG
Number of access zones	...	16	...
Bitrate	...	...	max. 256 Mbps
Supported hard drives	...	...	2 x 16 TB SATA
Number of alarm zones	...	16	...
Recording modes	...	...	Manual, Sensor, Motion detection, Schedule
Number of automation nodes	...	16	...
External storage devices backup	...	...	Backup to USB drive (pendrive, external drive)
Battery backup support	...	13.8 V / 7 Ah	...
Communication	...	<ul style="list-style-type: none"> <li>Ethernet 10BASE-T 10/100 Mb/s - RJ-45 socket</li> <li>2 x Port RS-485</li> <li>RACS (Roger)</li> </ul>	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Searching and playback the records	...	...	<ul style="list-style-type: none"> <li>Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>Advanced searching (to the one second accuracy)</li> <li>Smart Playback function</li> <li>Records playback from max. 16 channels in the same time @ 1080p (without AI)</li> <li>Records playback from max. 12 channels in the same time @ 1080p (AI)</li> </ul>
Network interface	...	...	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	...	Full support via network, Remote records copying, Web-Server built-in
Main features	...	<ul style="list-style-type: none"> <li>Control of automation from the system terminals</li> <li>Presentation of alarm supervision states on terminals</li> <li>Controlling the supervision state of the alarm system zones</li> <li>Hardware integration with alarm system and fire system</li> <li>Multifunctional parametric inputs including Double Wiring</li> <li>Weekly access schedules</li> <li>Multi-year calendars of exceptions</li> <li>Integrated support in VISO software</li> </ul>	...
Permissible relative humidity	...	≤ 95 % (non-condensing)	...
Network protocols	...	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register
ONVIF	...	...	22.06
Default IP address	...	...	192.168.1.108
Default admin user / password	...	...	admin / - The administrator password should be set at the first start
Mobile phones support	...	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>Android: Free application <a href="#">DMSS</a></li> <li>iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul> See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Web browser access ports	...	...	80, 37777
PC client access ports	...	...	37777
Mobile client access ports	...	...	37777
RTSP URL	...	...	<ul style="list-style-type: none"> <li>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=0 - Main stream</li> <li>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=1 - Sub stream</li> </ul>
USB	...	...	2 pcs USB 2.0
Serial ports	...	...	—
Alarm inputs / outputs	...	...	4 / 2
PTZ control	...	...	IP Speed Dome Cameras
Motion Detection	...	...	✓
Intelligent image analysis	...	...	✓



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	...	<ul style="list-style-type: none"> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, face detection</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles</li> <li>• Face recognition</li> <li>• Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask)</li> <li>• Support for up to 10 face databases, including 20 000 face images</li> <li>• In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number</li> <li>• Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity</li> <li>• Privacy zones</li> </ul> <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> <li>• ANPR</li> <li>• people counting</li> <li>• heat map</li> </ul>
Mouse support	...	...	✓
IR remote controller in the set	...	...	—
Power supply	...	<ul style="list-style-type: none"> <li>• 17 ... 18 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	12 V DC / 4 A (power adapter included)
Power consumption	...	...	max. 10 W (without HDD)
Operation temp	...	5 °C ... 40 °C	-10 °C ... 55 °C
Weight	...	0.15 kg	1.49 kg
Dimensions	...	175 x 72 x 30 mm	375 x 284 x 53 mm
Supported languages	...	...	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian
Manufacturer / Brand	KLIMAS	ROGER	DAHUA
Guarantee	2 years	3 years	3 years