




	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50PC2-28W</a> 2Mpx / 5Mpx 2.8 mm	<a href="#">SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE</a>	<a href="#">SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-SET 2 PCS SET ATTE</a>
			
	38.76 CAD 38.76 CAD	164.67 CAD 164.67 CAD	164.67 CAD 164.67 CAD
Standard	AHD, HD-CVI, HD-TVI	...	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...
Matrix size	5 Mpx	...	...
Connectors	...	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs cable terminal</li> <li>• 1 pcs BNC</li> </ul>	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm<sup>2</sup> ( 22 ... 12 AWG )</li> </ul>
LAN ports	...	1 pcs RJ45 100 Mbps	1 pcs RJ45 100 Mbps
Resolution	<ul style="list-style-type: none"> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ;</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps</li> </ul>	...	...
Lens	2.8 mm	...	...
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> <li>• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W (" +/-": 1, 2 pins; "+/-": 3, 6 pins) or (" +/-": 4, 5 pins; "+/-": 7, 8 pins)</li> <li>• xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W</li> </ul>	...
View angle	<ul style="list-style-type: none"> <li>• 95 ° (manufacturer data)</li> <li>• 103 ° (our tests result)</li> </ul>	...	...

Terminals	...	...	<p>ETH-2WIRE-TX :</p> <ul style="list-style-type: none"> <li>• PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul> <p>ETH-2WIRE-RX :</p> <ul style="list-style-type: none"> <li>• PoE OUT - Passive PoE ("+"-": 4, 5 pins; "-"-": 7, 8 pins)</li> <li>• Power</li> <li>• DATA - 2-wire</li> </ul>
Range of IR illumination	20 m	...	...
Transmission speed	...	...	100 Mbps
IR illuminator power adjustment	Automatic	...	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...	...
OSD menu	✓	...	...
Transmission range	...	<p>&lt; 1000 m @ Coaxial cable          &lt; 100 m @ xCOAX4-SW - Switch PoE          &lt; 100 m @ xCOAX4-CAM - IP Camera</p>	<ul style="list-style-type: none"> <li>• 300 m @ 2-wire : UTP,</li> <li>• 100 m @ 2-wire : OMY-2X0.75</li> <li>• 100 m @ UTP : Switch PoE - ETH-2WIRE-TX</li> <li>• 100 m @ UTP : ETH-2WIRE-RX - IP Camera</li> </ul>
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...
LED indicators	...	<ul style="list-style-type: none"> <li>• PoE</li> <li>• LAN</li> <li>• Link</li> <li>• 10Mb</li> </ul>	<ul style="list-style-type: none"> <li>• Power</li> <li>• LAN</li> <li>• 2-wire</li> </ul>
Color	White + Black	...	...
Operation temp	-20 °C ... 60 °C	...	...

Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, BNC</li> <li>• Short-circuit - xCOAX4-SW</li> </ul>	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, DATA</li> <li>• Protection against reverse polarity connection - Power</li> <li>• Overload 0.6 A - PoE IN ETH-2WIRE-TX</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Watchdog function - Coaxial cable</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Operation modes - Set with jumpers</li> </ul>
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...	...
Power supply	12 V DC / 300 mA	xCOAX4-SW : <ul style="list-style-type: none"> <li>• 10 ... 58 V DC - cable terminal</li> <li>• PoE 802.3af/at / PASSIVE</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>	ETH-2WIRE-TX : <ul style="list-style-type: none"> <li>• 44 ... 56 V DC - PoE</li> <li>• 24 ... 56 V DC - Power</li> </ul> ETH-2WIRE-RX : <ul style="list-style-type: none"> <li>• 24 ... 56 V - Power</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>
Power consumption	≤ 3.6 W	1.35 W (total)	1.35 W (total)
Housing	Compact - Plastic	Plastic (PC)	Plastic (PC)
"Index of Protection"	IP66	IP20	IP20
Operation temp	...	-25 °C ... 65 °C	-25 °C ... 65 °C
Weight	0.16 kg	0.033 kg (single element)	0.03 kg (single element)
Dimensions	162 x 70 x 70 mm	<ul style="list-style-type: none"> <li>• 73 x 52 x 20 mm - xCOAX4-SW</li> <li>• 73 x 52 x 20 mm - xCOAX4-CAM</li> </ul>	51 x 51 x 24 mm (single element)
Manufacturer / Brand	APTI	ATTE	ATTE
Guarantee	2 years	3 years	3 years