




| | POE SWITCH / EXTENDER PFT1310 3-PORT | KEYPAD FOR ALARM CONTROL PANEL INT- KLCD-BL SATEL | ADAPTER USB-W- MICRO/USB-G |
|----------------------|--|--|---|
| |  |  |  |
| | 18.69 CHF 18.69 CHF | 122.88 CHF 122.88 CHF | 0.51 CHF 0.51 CHF |
| Support | ... | INTEGRA, CA-64 | ... |
| Connector type | ... | ... | Adapter : Plug micro USB - B Socket USB - A |
| LAN ports | <ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af) | ... | ... |
| Main features | ... | <ul style="list-style-type: none"> • Blue backlight of the keys • 2 Inputs • LEDs indicating device operation state • Alarms: keypad hold-down PANIC, FIRE and AUX • Buzzer for acoustic signaling of some system events • Panel communication loss indication • RS-232 port allows to programming using the PC with GUARDX software installed • Microswitch as tamper contact | ... |
| Material | ... | ... | Metal / PET |
| Current consumption | ... | max. 101 mA | ... |
| Management | — | ... | ... |
| Operation temp | ... | -10 °C ... 55 °C | ... |
| LED diodes | LAN, PoE | ... | ... |
| Transmission speed | 10 / 100 Mbps | ... | ... |
| Manufacturer / Brand | ... | SATEL | ... |
| Maximal output power | <ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade | ... | ... |

| | | | |
|-------------------------------------|---|-------------------|--|
| Main features | <ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender | ... | <ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance |
| Power consumption | 0.3 W | ... | ... |
| Range | 100 m - Input 100 m - Output | ... | ... |
| Protections | Overvoltage | ... | ... |
| Housing | Plastic, DIN, TS-35 rail mounting | ... | ... |
| Power supply | PoE (802.3af/at) | 12 V DC | ... |
| Operation temp. / Relative humidity | -30 ... 65 °C / 10 ... 90 % | ... | ... |
| Weight | 0.05 kg | 0.23 kg | 0.007 kg |
| Dimensions | 79 x 52 x 23 mm | 140 x 126 x 26 mm | 49 x 18 x 11 mm |
| Guarantee | 2 years | 2 years | 2 years |