



	EXTENDER VGA + USB CE-100	LED LIGHTING CONTROLLER AD-TL-6497/T-S-5 V-24 V DC ORNO	IP CAMERA DS-2CD1023G2-1(4MM) - 1080p Hikvision	CABLES TESTER NS-468	SWITCHING ADAPTER PS65-15-DIN ACO	SWITCHING ADAPTER APS-053 SATEL	TELEPHONE PLUG RJ11*P100
							
	1108.84 DKK 1108.84 DKK	31.01 DKK 31.01 DKK	962.71 DKK 962.71 DKK	27.68 DKK 27.68 DKK	437.24 DKK 437.24 DKK	154.18 DKK 154.18 DKK	19.00 DKK 19.00 DKK
Standard	TCPIP
Application	...	Works with LED lighting	ACO Video Doorphones
Adapter type	Switching	Switching	...
Sensor	1/2.9" Progressive Scan CMOS
Rated voltage	...	5 V - 24 V DC
In package	100 pcs The price for package
Matrix size	2.1 Mpx
Power voltage	100 ... 240 V AC	195 ... 265 V AC	...
Frequency range	50 Hz	...
Output voltage adjustment	---	---	...
Tested cables	UTP, FTP, YTKSY - RJ45 (6P6C), RJ11 (6P4C), RJ12 (6P6C)
Output voltage	15 V DC	5 V DC, stabilized	...
Maximal load	4 A	0.5 A	...
Connector type	RJ 11 Plug 4 pin
Output power	65 W	4 W	...
Attachment of connector elements	Crimping
Maximal total load	...	• 5 V = 40 W • 12 V = 96 W • 24 V = 120 W
Wire mounting	Crimping
Lens	4 mm
Efficiency	≤ 91 %	≤ 72 %	...
Total maximal current	...	8 A
Application	Twisted-pair cable
Number of inputs	...	0
Material	PET
Number of outputs	...	1	2 pcs	2 pcs	...
View angle	• 81 ° (manufacturer data) • 76 ° (our tests result)
Example of application	• UTP cat. 5e
Connector type	...	PCB (soldering)
Range of IR illumination	30 m
Wireless	...	---	---
Memory card slot	...	---	---
Protections	• Short-circuit • Overload • Overheat	• Input : Short-circuit, DC filter to eliminate interferences • Output : Short-circuit, Overload	...
Environment class	II	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Housing type	DIN	Plastic	...
Alarm inputs / outputs	---
Audio	---
Operation temp	-10 °C ... 55 °C	...
Main stream frame rate	25 fps @ 1080p
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
Device type	Active / Transmitter
ONVIF	Active / Receiver	...	18.12
Mobile phones support	---	---	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Number of channels	1 x VGA 2 x USB 1 x VGA 2 x USB
Default admin user / password	admin / -
Default IP address	192.168.1.64
Video transmission range	max. 100 m max. 100 m
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
Connectors type	1 x VGA Socket HDB-15 2 x USB-A Socket 1 x VGA Plug HDB-15 1 x USB-B Socket
Symmetrical socket type	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	<ul style="list-style-type: none"> Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main features	<ul style="list-style-type: none"> Real-time DDC communication support Built-in ESD protection 8 15 kV Manual compensation adjustment Possibility to mount to the wall 	<ul style="list-style-type: none"> High power - max. 120 W Possibility to adjust the light intensity depending on your needs Works with lampshades made of plastic Small dimensions Possible assembly in a profile Simple and quick device installation 	<ul style="list-style-type: none"> IEC 38 compliance Can be installed in a 60mm electrical box 	<ul style="list-style-type: none"> Very easy and quick assembly To crimp use the crimping tool HT-546
Main features	<ul style="list-style-type: none"> D-WDR - Wide Dynamic Range 3D-DNR - Digital Noise Reduction ROI - improve the quality of selected parts of image Anti-Flicker - The technology eliminates the tiring eyes flickering image effect EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners BLC - configurable Back Light Compensation HLC - High Light Compensation (spot) ICR - Movable InfraRed filter Day/night mode Mirror - Mirror image Configurable Privacy Zones Smart motion detection (with recognizing people and vehicles) Sharpness - sharper image outlines
Power supply	5 V / 1000 mA 5 V USB	...	<ul style="list-style-type: none"> PoE (802.3af), 12 V DC / 410 mA 	Battery 9 V 6LR61 (not included)
Resolution	<ul style="list-style-type: none"> 1920 x 1080 / 60 Hz @ 30 m 1920 x 1200 / 60 Hz @ 30 m 1280 x 1024 / 60 Hz @ 100 m 	...	1920 x 1080 - 1080p , 1280 x 720 - 720p
Power consumption	<ul style="list-style-type: none"> ≤ 5 W @ 12 V DC ≤ 6.5 W @ PoE (802.3af)
Housing	...	---	Compact - Metal + Plastic
Color	...	---	White
"Index of Protection"	...	IP20	IP67
Operation temp	-30 °C ... 60 °C
Weight	0.170 kg 0.170 kg	0.001 kg	0.27 kg	0.12 kg	0.22 kg	0.036 kg	0.001 kg
Dimensions	91 x 56 x 25 mm 91 x 56 x 25 mm	49 x 10 x 4 mm	171 x 70 x 66 mm	101 x 107 x 28 mm	70 x 91 x 59 mm	47 x 47 x 22 mm	14.5 x 9.5 x 11 mm
Supported languages	Polish, English, Croatian, Czech, Romanian, Serbian, Slovak, Slovenian, Turkish, Ukrainian, Vietnamese
Manufacturer / Brand	...	ORNO	Hikvision	...	ACO	SATEL	...
SAP Code	311320658
Guarantee	2 years	2 years	3 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00