

	CABLES TESTER CS-NT24-PRO	POWER CORD CABLE CEE-716/IEC-C7-3M 3 m	ROUTER RG-EG209GS REYEE
			
	202.31 EUR 202.31 EUR	2.23 EUR 2.23 EUR	158.89 EUR 158.89 EUR
Cable	...	IEC320 C7 socket / CEE-716 plug	...
Length of the cable	...	3 m	...
Voltage	...	max. 250 V	...
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z
Tested cables	STP / UTP cat. 5, 5e, 6, 6e - RJ45 (8P8C), RJ11 (6P4C), Coaxial cable
LAN ports	<ul style="list-style-type: none"> • 7 x LAN 10/100/1000 Mbps (RJ-45) • 2 x LAN/WAN 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 1000 Mbps - port SFP
WAN interface	<ul style="list-style-type: none"> • 1 x WAN x 10/100/1000 Mbps (RJ-45)
Typical battery charge time	3 h
Backup time	16 h
LED indicators	Status, Link/Act
DDNS	✓
DHCP server	✓
Port USB	—
Firmware update	✓
Power supply PoE	—
Protections	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NATP • Port Mapping
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Management System • Configuration using the Ruijie Reyee application • Remote management • Web browser

Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Main features	<ul style="list-style-type: none"> • 2.4 " LCD display - 320 x 240 px • Cable test and cable tracer : cable type, UTP cable's sequence and type test, the fault of RJ45 connector • Test TDR - RJ45 : pair status, length, attenuation, reflectivity, impedance, skew - Length of the cable max. 180 m • Test TDR 2.0 : Searching for a wire fault point - Length of the cable max. 1200 m, • Detection of the connected port in switch • Test PING : correct operation of the IP camera's Ethernet port, correct IP address • IP Scan • Identification of the network port and duplex mode • Identification the wire in the group of wires • Telephone line condition detection • Detecting and locating a cable break or short circuit • HD coaxial video level meter • Automatic power-off : 10 ... 120 minutes 	<ul style="list-style-type: none"> • Solid workmanship • 2 x 0.75 mm² 	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button
Power supply	Cables tester : Li-Ion battery 3.7 V / 2000 mAh, USB DC 5V/2A power adapter (included) Probe : 2 x 1.5V, type AA/LR6/FR6 battery (not included)	...	12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 18 W
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.34 kg - Cables tester 0.11 kg - Probe	0.11 kg	0.54 kg

Dimensions	175 x 88 x 40 mm - Cables tester 220 x 47 x 32 mm - Probe	...	202 x 110 x 29 mm
Manufacturer / Brand	RUIJIE / REYEE
Guarantee	2 years	2 years	2 years