


	<a href="#">IP CAMERA DS-2CD2T46G2P-ISU/SL(2.8MM)(C) PANORAMIC ACUSENSE - 4.1 Mpx 2 x 2.8 mm Hikvision</a>	<a href="#">MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD</a>
		
	672.56 AUD 672.56 AUD	16.02 AUD 16.02 AUD
Standard	TCP/IP	...
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	10 A
Maximal total load	...	2300 W
Sensor	2 x 1/2.5 " Progressive Scan CMOS	...
Response time	...	< 25 ns
Number of outlets	...	2 grounded outlets 10A/250V
Matrix size	2 x 2 Mpx - 4.1 Mpx (total)	...
Maximal voltage	...	250 V / 50 Hz
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Resolution	3140 x 1368 - 4.1 Mpx	...
Nominal stroke current	...	2 kA (L/N) - (8/20µs)
Lens	2 x 2.8 mm	...
Maximum stroke current	...	10 kA (L/N) - (8/20µs)
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains
View angle	180 ° (horizontal) 44 ° (vertical)	...
Range of IR illumination	40 m	...
RS-485 interface	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Digital Noise Reduction</li> </ul>	...
Main stream frame rate	25 fps @ 4.1 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...

Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Main features	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 4 LEDs</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• 12 V DC / 880 mA,</li> <li>• PoE (802.3af)</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 10.5 W @ 12 V DC</li> <li>• ≤ 12.5 W @ PoE</li> </ul>	...
Housing	Compact, Metal	Plastic - non-flammable
Color	White	...

Vandal-proof	—	...
"Index of Protection"	IP67	...
Operation temp	-30 °C ... 60 °C	...
Weight	1.43 kg	0.12 kg
Dimensions	119 x 105 x 307 mm	131 x 55 x 75 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
SAP Code	311320496	...
Manufacturer / Brand	Hikvision	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00