




	DOOR FOR 48-MODULAR DISTRIBUTION CABINETS LE-337252 XL³ S 160 LEGRAND	DOOR FOR 72-MODULAR DISTRIBUTION CABINETS LE-337253 XL³ S 160 LEGRAND	SMART THERMOSTAT THERMOBOX/BLEBOX Wi-Fi, 230 V AC
			
	83.80 EUR 83.80 EUR	55.83 EUR 55.83 EUR	52.15 EUR 52.15 EUR
Application	Distribution cabinets 2 x 24-modular - XL ³ S 160	Distribution cabinets 3 x 24-modular - XL ³ S 160	switching heating devices on/off
Rated voltage	230 V AC
Transparent door	—	—	...
Maximal total load	3680 W / 3680 VA
Total maximal current	16 A
Number of inputs	1
Number of outputs	1
Material	Steel	Steel	...
Connector type	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Safety class	Grade 2	Grade 2	...
Compliance with standards	IEC 60695-2-1	IEC 60695-2-1	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS

Main features	<ul style="list-style-type: none"> • Reversible door • 1 closing point • Supplied with handle in the kit 	<ul style="list-style-type: none"> • Reversible door • 1 closing point • Supplied with handle in the kit 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support, • Waterproof probe - the ability to measure water temperature • Maximum number of connected probes : 2 - main probe (included), optional safety probe, • Measurement range : -55 ... 125 °C • Measuring accuracy : 0.5 °C (-10 ... 85 °C) • Autonomous operation • self test feature • Boost mode - heat up or cool down faster for a specific period of time
Housing	Plastic
"Index of Protection"	IP20
Color	White	White	Black
Operation temp	-20 °C ... 50 °C
Weight	2.724 kg	3.622 kg	0.07 kg
Dimensions	547 x 394 x 27 mm	547 x 544 x 27 mm	<ul style="list-style-type: none"> • 47 x 42 x 22 mm • Ø 6 x 30 mm - Probe • 1 m - Length of the cable (Probe)
Manufacturer / Brand	LEGRAND	LEGRAND	BleBox
Guarantee	2 years	2 years	2 years