

	<a href="#">TWILIGHT SWITCH FOR LED LIGHTING TWILIGHT-COMPACT/BLEBOX 12 ... 24 V DC</a>	<a href="#">ACCESS CONTROLLER ASC2202B-S DAHUA</a>	<a href="#">EXTENDER VGA TRVGA-300-P</a>
			
	13.02 GBP 13.02 GBP	179.88 GBP 179.88 GBP	103.13 GBP 103.13 GBP
Number of served transitions	...	2 (one-way)	...
Support	...	DAHUA	...
Application	Works with LED lighting - 12-24V LED strips	...	...
Number of supported readers	...	4 pcs	...
Battery backup support	...	—	...
Rated voltage	12 ... 24 V DC	...	...
Output lines	...	2 pcs - Relay	...
Maximal total load	60 ... 120 W	...	...
Total maximal current	5 A	...	...
Number of inputs	0	...	...
Number of outputs	1	...	...
Connector type	screw terminals	...	...
Communication	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand</li> </ul>	...
Wireless	—	...	...
Mobile phones support	—	...	...
Device type	...	...	<b>Active / Transmitter</b> <b>Active / Receiver</b>
Number of channels	...	...	1 VGA 1 VGA
Default IP address	...	192.168.0.2	...
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 4 A</li> </ul>	12 V / 70 mA (power adapter not included) 12 V / 170 mA (power adapter not included)
Housing	Self-extinguishing	...	...
Video transmission range	...	...	max. 300 m max. 300 m
Default admin user / password	...	admin / - The administrator password should be set at the first start	...

"Index of Protection"	IP20	...	...
Symmetrical socket impedance	...	...	100 Ω 100 Ω
Color	Black	...	...
Operation temp	-20 °C ... 50 °C	-30 °C ... 60 °C	...
Permissible relative humidity	...	5 % ... 90 % (non-condensing)	...
Connectors type	...	...	VGA Socket VGA Socket female
Symmetrical socket type	...	...	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket
Weight	0.008 kg	0.27 kg	0.078 kg 0.078 kg
Dimensions	23 x 17 x 22 mm	155 x 116 x 50 mm	118 x 30 x 48 mm 118 x 30 x 54 mm
Main features	<ul style="list-style-type: none"> <li>• High power - max. 120 W,</li> <li>• Automatic calibration,</li> <li>• Mild lightening at dusk,</li> <li>• Mild darkening at dawn,</li> <li>• Small dimensions</li> </ul>	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 500000 events</li> <li>• Remote programming from PC</li> <li>• Function of protection against multiple use of the same card for access (anti-passback)</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> </ul>	<ul style="list-style-type: none"> <li>• Short-circuit protection</li> <li>• Signal correction</li> </ul>
Resolution	...	...	<ul style="list-style-type: none"> <li>• 1920 x 1200 / 80 Hz @ 100 m</li> <li>• 1024 x 768 / 60 Hz @ 300 m</li> </ul>
Manufacturer / Brand	BleBox	DAHUA	DELTA
Guarantee	2 years	3 years	3 years